

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well ☒ other
2. NAME OF OPERATOR
Northwest Pipeline Corporation
3. ADDRESS OF OPERATOR
P.O. Box 90, Farmington, N.M. 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1885' FNL & 1165' FEL
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:


- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☒ Drlg Operations

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED
APR 27 1981

(NOTE: Report results of multiple completion or change on Form 9-331-C)



5. LEASE
SF 078917
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 29-5 Unit
8. FARM OR LEASE NAME
San Juan 29-5 Unit
9. WELL NO.
#100
10. FIELD OR WILDCAT NAME
Gobernador PC/ Blanco MV
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 25, T29N, R5W
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
30-039-22534
15. ELEVATIONS (SHOW DF, KDB, AND WD)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-17-81 Ran 105 jts of 7", K-55, ST&C & set at 4080'. Cmt'ed w/ 85 sx 65/35 poz w/ 12% gel. Tailed w/ 75 sx C1 "B" w/ 2% CaCl₂. Displaced w/ 165 bbls wtr & down at 1430 hrs. Did not circulate cmt behind 7" csg. Calculated top of cmt at 2915'.

4-18-81 to 4-19-81 drlg to a depth of 5900'.

4-20-81 Reached TD of 6195. Ran IES, Neutron Density Gamma Ray logs. Ran 73 jts (2311') of 4-1/2" 10.5#, K-55, ST&C & set from 6195' to 3884'. Dowell cmt'ed w/ 230 sx C1 "B" w/ 4% gel. & 12-1/2# gil/sx. Displaced plug w/ 159.5 bbls wtr. Down at 0545 hrs 4-20-81. Reversed out 1/2 bbl. Rig released at 1000 hrs 4-20-81.

NOW WAITING ON COMPLETION.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Donna J. Brace TITLE Production Clerk DATE 4-27-81
Donna J. Brace
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

APR 30 1981

NMOCC

*See Instructions on Reverse Side

FARMINGTON DISTRICT

djb/