

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Northwest Pipeline Corporation

3. ADDRESS OF OPERATOR
P.O. Box 90, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1885' FNL & 1165' FEL
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other)

SUBSEQUENT REPORT OF

RECEIVED

JUN 10 1981

U S GEOLOGICAL SURVEY
FARMINGTON, N.M.

5. LEASE
SF 078917

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
San Juan 29-5 Unit

8. FARM OR LEASE NAME
San Juan 29-5 Unit

9. WELL NO.
#100


10. FIELD OR WILDCAT NAME
Gobernador PC / Blanco MV

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 25, T29N, R5W

12. COUNTY OR PARISH | 13. STATE
Rio Arriba | N.M.

14. API NO.
30-039-22534

15. ELEVATIONS (SHOW DEPTH AND WD)
6795' CR



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 6-7-81 MOL & RU.
- 6-8-81 PU 3-7/8" bit & drld cmt from 5789' - 6118'. Press test csg to 3500# for 10 min - OK. Circ hole & spot 750 gal of 7-1/2% HCl. Blue jet ran GR/CC1 & perfed 24 holes from 5610' to 6070'. Smith pumped 1000 gal 7-1/2% HCl & dropped 50 balls. Rank junk basket & rec'ed 15 balls w/ 5 hits.
- 6-9-81 Mesa Verde Smith fraced w/ 10,000 gal pad followed w/ 80,000# 20/40 sand @ 1-2 ppg. MIR 50; AIR 50; MIP 3200; AIP 2800. ISIP 200#, 0# in 5 min. Job done @ 0845 hrs. Set bridge plug @ 4000' - tested to 3500# - OK. Pictured Cliffs - Blue Jet perfed 12 holes from 3638' - 3795'. Smith spear-headed 500 gal 7-1/2% HCl. Fraced w/ 5000 gal pad followed w/ 50,000 10/20 sand @ 1/2 - 1-1/2 ppg. MIR 41, AIR 41, MIP 3100#; AIP 2600. ISIP 500#; 500# in 15 min. Job done @ 1410 hrs. Tagged 40' sand in btm.
- 6-10-81 Blowing down Pictured Cliffs w/ compressor.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Donna J. Brace TITLE Production Clerk DATE 6-10-81

(This space for Federal or State office use)

RECEIVED FOR RECORD

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

JUN 15 1981

MOC

*See Instructions on Reverse Side

BY Dean Elliott

djb/

