

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS


(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Southland Royalty Company
3. ADDRESS OF OPERATOR  
P.O. Drawer 570, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2010' FNL & 1120' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | REQUEST FOR APPROVAL TO:                      | SUBSEQUENT REPORT OF:    |
|---|--------------------------|
| TEST WATER SHUT-OFF <input type="checkbox"/>  | <input type="checkbox"/> |
| FRACTURE TREAT <input type="checkbox"/>       | <input type="checkbox"/> |
| SHOOT OR ACIDIZE <input type="checkbox"/>     | <input type="checkbox"/> |
| REPAIR WELL <input type="checkbox"/>          | <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE <input type="checkbox"/>    | <input type="checkbox"/> |
| CHANGE ZONES <input type="checkbox"/>         | <input type="checkbox"/> |
| ABANDON* <input type="checkbox"/>             | <input type="checkbox"/> |
| (other) Casing Rpt                            | X                        |

5. LEASE  
NM-0558139
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Creek
9. WELL NO.  
2
10. FIELD OR WILDCAT NAME  
Blanco Pictured Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 4, T29N, R5W
12. COUNTY OR PARISH  
Rio Arriba
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6343' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12/19/80 Ran 79 joints (3436.44') of 4-1/2", 10.5#, K-55 casing set at 3448'. Cemented with 210 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# flocele per sack followed with 50 sacks of Class "B", displaced with 200 gals 7-1/2% acetic acid. Plug down at 3:30 A.M. 12-20-80.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Charles Traynor TITLE Drilling Clerk DATE December 22, 1980

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL JAN 8 1981

BY BW FARMINGTON DISTRICT