Dec. 1973	Budget Bureau No. 42-R1424			
UNITED STATES	5. LEASE			
DEPARTMENT OF THE INTERIOR	SF-079757A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
GEOLOGICAL SURVEY				
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME San Juan Unit 29–4			
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)				
reservoir, use rorm 9-331-C for such proposals.)	8. FARM OR LEASE NAME			
1. oil gas XX well other	9. WELL NO.			
2. NAME OF OPERATOR	24			
Amoco Production Company	10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR	Basin Dakota			
501 Airport Dr., Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA NW/4, NE/4, Section 8,			
below.)	T29N, R4W			
AT SURFACE: 1220 FNL x 2250 FEL AT TOP PROD. INTERVAL: Same	12. COUNTY OR PARISH 13. STATE			
AT TOTAL DEPTH: Same	Rio Arriba NM			
16 CUECK APPROPRIATE DON TO INDICATE MATURE OF MOTIOE	14. API NO. 30-039-22844			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA				
REPORT, OR OTHER DAW	15. ELEVATIONS (SHOW DF, KDB, AND WD)			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	7400 01			
TEST WATER SHUT-OFF	· · · · · · · · · · · · · · · · · · ·			
FRACTURE TREAT				
SHOOT OR ACIDIZE	The second second			
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone thange on Form ∮-330.)			
MULTIPLE COMPLETE	rangan di kacamatan			
CHANGE ZONES	Commence of the commence of th			
ABANDON* [X]	1997 39 J			
(other) PxA Dakota	<i>I</i>			
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent	lirectionally drilled, give subsurface locations and			
Amoco Production Company abandon the Dakota for 10-21-82 following verbal permission by Errof Amoco. The well was plugged and abandon in the Dakota straightful and the principle of Straightful and the principle of Straightful and Straight	rrol Becker to Mr. A. M. Montoya in the following manner:			

1) Drilled out bridge plug at 8100'.

- 2) Pushed bridge plug by wireline to 8540'.
- 3) Packed 3 sx, (4 cu ft) class B neat cement above the bridge plug and provided a seal.

Subsurface Safety Valve: Manu. and Type 18. Thereby certify that the foregoing is true and correct					Set @	Ft.	
					ζ.		
www.tD	Original Signed By B.T. Roberson	TITLE	Admin. Super	•	3-11-33		
		(This space	Far Fritzenstein Comment				
APPROVED BY CONDITIONS OF	F APPROVAL, IF ANY	TITLE	<u>:</u>	DATI			

AGGEPTED FOR RECORD

MAI

1983

NMOCC