

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL ☐ GAS ☒ OTHER ☐

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P. O. Drawer 570, Farmington, New Mexico 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1070' FSL & 1835' FEL

5. LEASE DESIGNATION AND SERIAL NO.

NM-0558140

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

La Jara

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Gobernador Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 10, T29N, R5W

14. PERMIT NO.

15. ELEVATIONS (Show whether OP, ST, GR, etc.)

6427' GL

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Completion Reports

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

9/25/84 MIRU Spartan Rig #1 on 9-25-84.
Pressure tested 4-1/2" casing to 3500 psi-OK.
Perforated Pictured Cliffs with 24 Holes at 3236', 3245', 3250', 3258',
3265', 3274', 3281', 3292', 3312', 3319', 3325', 3338', 3344', 3350', 3356',
3364', 3374', 3382', 3388', 3394', 3400', 3410', 3416', 3422'.
Fraced with 175,000 gals slick water and 160,000# of 20/40 sand.
AIR 63 BPM, ATP 1950 psi, ISIP 550 psi.

9/28/84 Landed 105 joints (3304') of 2-3/8", 4.7#, J-55 tubing at 3316' with
seating nipple at 3286'.
Rel rig on 9-28-84 and Well SIFT.

RECEIVED
OCT 22 1984
OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Catherine Greyson

TITLE

Secretary

DATE

10/02/84

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OCT 14 1984

*See Instructions on Reverse Side

PERMITS SECTION AREA
RV *Smith*