

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-039-24521
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name San Juan 29-6 Unit
8. Well No. #206
9. Pool name or Wildcat Basin Fruitland Coal
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6363' GR 6376' KB

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator Northwest Pipeline Corporation
3. Address of Operator 3539 East 30th Street - Farmington, NM 87401
4. Well Location Unit Letter H : 1390 Feet From The North Line and 1090 Feet From The East Line Section 4 Township 29N Range 6W NMPM Rio Arriba County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6363' GR 6376' KB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Drilling Operations ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-30-89: MOL & RU.

12-1-89: Spudded well at 1800 hrs 12/1/89. Drilled 285' of surface hole. TOH w/ DCs. Ran 6 jts (265') 13-3/8", 48#, H-40, ST&C Hoesch csg. Set at 278' KB. Cemented w/ 315 sx (378 cu.ft.) Cl "B" w/ 3% CaCl₂ & 1/4# cele-flake/sk. Displaced w/ 31.5 bbls wtr. Good circulation throughout job. Circulated 4 bbls good cement to surface.

12-2-89: Plug down at 0400 hrs. WOC.

12-3 & 12-4: Drilling w/ Benex.

(continued on back)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Carrie Harmon TITLE Production Assistant DATE _____
TYPE OR PRINT NAME Carrie Harmon TELEPHONE NO. 327-5351

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT #: _____ DATE MAR 13 1990
CONDITIONS OF APPROVAL, IF ANY: