

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

PHILLIPS PETROLEUM COMPANY

3. Address and Telephone No.

300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit G 1375' FNL & 1815' FEL

S 17, T29N, R6W

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
SF-078278

6. If Indian, Allottee or Tribe Name
--

7. If Unit or CA, Agreement Designation
San Juan 29-6

8. Well Name and No.
226

9. API Well No.
30-039-24668

10. Field and Pool, or Exploratory Area
Basin Fruitland Coal

11. County or Parish, State
Rio Arriba

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other As Per NTL-FRA-90-1

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1.

Date: 6/25/90 Time Started: 1004 Time Completed: 1102
Hole Size 8-3/4 Casing Size 7" 23# J-55 New Casing Seat 3478 Ft.
Turbo Centralizers at 2920, 2876, 2831.
Spring Type Centralizers at 3465, 3394, 3305, 3216, 3132.
Mud Flush 10 Bbls, Spacer 10 Fresh Water.

Lead Slurry 500 sx 65/35 C. "B", 12% Gel, 1/4#/sx Flocele, 11.7 ppg @ 2.30 ft³/sx yield.

Mid Slurry 100 sx Standard, 1/4"/sx Flocele, 15.6 ppg @ 1.18 ft³/sx yield.

Tail Slurry 50 sx Standard, .7% CFR-3, 17.5 ppg @ .95 ft³/sx yield.

Displaced Plug with 133 Bbls Fresh Water.

Volume Cement Circulated 60 Bbls/Sand

Average Pressure 450 PSI, Average Rate 4 BPM, Bumped Plug with 1500 PSI.

14. I hereby certify that the foregoing is true and correct

Signed

R. A. Allred

Title

R. A. Allred
Drilling Supervisor

Date

9-12-90

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

Date

SEP 26 1990

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side