

NOTE:


**OPERATOR WANTS
RECOMPLETION OF NACIMIENTO
FORMATION AS TIGHT HOLE,
“CONFIDENTIAL FOR 1 YEAR.**

**THE SUNDRY FOR RECOMPTION
RECEIVED 1-28-02 IS IN
CONFIDENTIAL FILE.**

Location Dimensions 210' X 250'

Plat #3 Location Diagram

January, 2002
John Thompson



Williams Production Company

Rosa Unit #375

1675' fsl & 1875' fwl, Sec 24, T31N, R5W
Rio Arriba County, New Mexico

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir
Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Synergy Operating, LLC

3. Address and Telephone No.

PO Box 5513 (505) 325-5449
Farmington, NM 87499

4. Location of Well (Footage, Sec. T. R., M, or Survey Description)

1905' FSL & 1604' FWL Sec 28, T29N, R04W

5. Lease Designation and Serial No.

NMMN-18327

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

29-4 Carson 28 # 1

9. API Well No.

30-039-2467300

10. Field and Pool, or Exploratory

Wildcat NACIMIENTO (GAS)

11. County or Parish, State

Rio Arriba County
New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☒ Plugging Back
☐ Casing Repair
☒ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well
Completion or recompletion Report and Log Form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including, estimated date of starting work.
If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones of pertinent to this work.

Synergy Operating, LLC is in receipt of a letter dated April 11, 2002 from the Aztec Office of the NMOCD regarding this well.

Synergy has evaluated the currently open San Jose Formation, and we have determined it to be water productive. The water is fresh in nature and the Carson Forest Service should consider this zone prospective for a future water supply.

In order to comply with NMOCD well standards, Synergy is planning to Officially Temporarily Abandon this wellbore per the attached procedure.

THIS APPROVAL EXPIRES JUL 01 2003

Synergy believes that there may be future potential to drill out the bridge plugs and cement plugs currently in the well and run a string of 3-1/2" casing and cement the well as a Pictured Cliffs/Fruitland Coal Commingled Producer. Synergy is evaluating offset completion activity in the Fruitland Coal to judge the economic viability of this idea.

Until this evaluation is complete, Synergy Operating will maintain the subject wellbore in an Official Temporary Abandoned State.

This sundry amends the Sundry Noticed dated 06-11-2002 submitted by Glen Papp of our office.

14. I hereby certify that the foregoing is true and correct

Signed:

Thomas E. Mullins

Title: Engineering Manager

Date: 06-18-2002

This space for federal or state office use

Approved by:

Conditions of approval if any

Title:

Date:

6/26/02

PROCEDURE TO: Temporarily Abandon Wellbore

Carson 29-4 28 #1

Well History: The Carson 29-4 28 #1 was drilled as a Fruitland Coal producer in July of 1990 by Falcon Seaboard Oil & Gas. 5-1/2" 17# N-80 casing was set at 4497' and cemented in 2-stages: 1st Stage – 200-sxs 50/50 Poz, F/B 225-sxs CI 'B' ; 2nd Stage thru DV tool @ 2030' w/ 350-sxs HOWCo Lite Cmt, F/B 50-sxs CI 'B'. In October 1990, remedial cement was placed through squeeze holes at 1560', with a temperature survey identifying the TOC @ 500'. The Fruitland Coal formation had an initial SICP of 1080 psi, and produced at an initial rate of 60 MCFD & 10 BWPD. A pump jack was utilized initially until June of 1991. At this time a plunger lift system was installed in conjunction with a wellsite compressor. Parriffin production and coal fines production was noted. The well produced at a rate of 130 MCFD with the plunger. In October 1991, the plunger lift was removed from the well and the rod pump installed again. Production rates were now 50 MCFD & 3 BWPD. The Fruitland Coal had cumulative production of 20 MMCF at time of abandonment in October 1995.

A CIBP was placed at 4000' to abandon the Fruitland Coal in 1995, and an attempt was made to complete the Ojo Alamo and the Nacimiento formations. These tests were unsuccessful. Additional CIBPs were placed at 3700', 2928', and a cement plug placed below a retainer at 3520'. Synergy acquired this wellbore and set an additional CIBP @ 2820', and made an additional attempt to complete the Nacimiento. It was unsuccessful. A CIBP was placed at 2500', and an attempt was made to complete in the San Jose formation in August 2000. This zone was water productive. The wellbore currently has 2-7/8" tubing and 7/8" sucker rods and a insert rod pump in the well and no surface equipment.

NOTE: All depths are referenced to a KB elevation of 7414' (13' above graded ground elevation of 7401').

1. If any excavation is necessary to facilitate the workover activities, notify Glen Papp or Larry Starkey w/ L&R Anchor Service for a One Call, a minimum of 48 hours prior to commencing any work.
2. Assuming Level III Fire Restrictions are in place, notify Forest Service at 632-1963 prior to MIRU. **SEE NOTE BELOW regarding fire prevention equipment.** Access to the wellsite is through a locked gate.
3. Locate nearest area that an emergency rescue helicopter can land and document approximate distance and direction from well pad on Emergency Response page located at the back of this procedure.
4. Assuming Level III Fire Restrictions are in place, must have 80-Bbls Fresh Water on location and at least 300' of fire hose (1-1/2" minimum diameter) and a method of pumping it.
5. Ensure that well is shut in, locked and tagged out. (Currently disconnected from Williams Pipeline).

6. Hold Pre-Job Safety Meeting. Review planned activity.
7. Record casing pressure, blow down well (Well should be dead).
8. MIRU Well Service Rig and associated equipment. Three Rivers Pump Truck on location (36 bbls), with Water Truck (80 bbls) to arrive for rolling the hole to meet fire watch requirements. Fire prevention equipment to be on location throughout well operational work.
9. COOH, laying down 81-7/8" sucker rods and 2-1/2"x1-1/4"x14'x18' RHAC pump. (Pump to be returned to Energy Pump & Supply). Rods laid on boards by WH.
10. ND B-1 Adapter Flange. NU BOPE. Function Test.
11. COOH w/ 69-Jts 2-7/8" tubing, laying down SN, perf sub and 1-Jt 2-7/8" tbg used as Mud Anchor.
12. TIH w/ 5-1/2" 17# CIBP & setting tool on 2-7/8" tubing & set @ 1825'+/-, above San Jose (Top perf @ 1906').
13. Circulate hole with water, 43 bbls+/-.
14. Pressure Test CIBP & Entire Casing String to 500# for 30-Minutes as per NMOCD guidelines. COOH w/ setting tool.
15. GIH with 2-7/8" tbg, SN up one jt, Land Tubing @ 1750'+/- above CIBP.
16. ND BOPE. RD Well Service Rig.


Carson 29-4 2B # 1

Unit K, Section 28-T29N-R04W
1905' FSL, 1604' FWL
7401' GL, 13' KB

Araphoe # 7
Bayless Rig # 6

Spud: 07/21/90
Completed: 11/7/90

API # 30-038-2467300



8-5/8" 24# K-55 Casing @ 259' w/ 210 sxs
Circulated 6 bbls cement to surface
Cement Fell Back, Cmt 30 sxs down annulus

2-7/8" 6 5# J-55 Tubing @ 2901', SN one ft up (69 its) @ 2101'
2" x 1-1/4" Pump & 81 -7/8" Rods

2 Sqz Holes @ 1560', Cemented w/ 300 sxs. TOC Temp Survey 500' +/-

DV Tool @ 2033' (See Cmt Detail Below)

CIBP @ 2500'

CIBP @ 2820'

CIBP @ 2928'

Cmt Retainer @ 3520' (Cmt from 3515' to 3613')

CIBP @ 3700'

CIBP @ 4000'

San Jose Perforations (Currently Open)
1906'-1912' & 1922'-1928' Frac 2/ 2K 20/40 in 70Q N2 Foam

Nacimiento Perforations
Open Perfs from 2602' to 2880'. A portion of perfs from 2602' to 2741' Frac w/ 2K 20/40 in 70Q N2 Foam

Fruitland Coal Perforations
Upper: 4086'-4088', 4130'-4139' (10 Holes) Frac w/ 10K 40/70 & 11K 20/40 in 70Q N2 Foam (Screen Out)
Lower: 4164'-4190' (18 Holes) Frac w/ 20K 40/70 & 120K 20/40 in 70Q N2 Foam

5-1/2" 17# N-80 Casing @ 4496', w/ 1st Stage w/ 200 sxs 50/60 Poz 2% gel 0.6% Halad 322
tail with 225 sxs B w/ 0.4% Halad 344, 0.4% CFR-3 & 2% Super CBL
Circulate 3 hrs, 2nd Stage w/ 350 sxs Howco Lite 0.6% Halad 322, 2% KCl and 1/4# Flocel,
tail with 60 sxs B neat. Lost Circulation 28 bbls into Displacement.

Formation Tops	
San Jose Surf	
Nacimiento	
Ojo Alamo	3642'
Kirtland	3862'
Fruitland	3980'
Pict Cliffs	4192'
Lewis	4440'

Formation Name: Fruitland Coal

Drill out DV Tool, CO to PBTD 4456', RU Basin, Run GR-CCL-CBL 4438' to 1800'.
Spot 7-1/2% HCl acid across Coal zone. Perforate 4164', 4166', 4167', 4168', 4170', 4171', 4172', 4176', 4178', 4179', 4181',
4182', 4183', 4184', 4185', 4186', 4189', 4190' (18 holes) -0.38". Opened well the next AM, Hydrocarbons unloaded
to the pit and caught fire, burned off. GIH w/ SPIT tool, set across each perf and establish communication on all.
Set tool @ 4116', RU to swab. Making Gas after 5th run. COOH w/ tool. RU to Frac. Smith Energy Frac Lower Coal
w/ 20K 40/70 sand & 120K 20/40 sand in 70Q N2 at 45-55 BPM 2600 ATP, ISIP 1600 Foam Flush, SI 2-hrs flowback on 1/4" choke
Well making 5% Paraffin, Tag Sand Fill @ 4390', CO fill. RU Basin, Set 5-1/2" RBP @ 4150', PT 3000 psi Okay. GIH and Spot 7-1/2% HCl
Acid across Upper Coal perforations. Perforate Upper Coal interval at 4087', 4088', 4130', 4131', 4132', 4133', 4134', 4137', 4138', 4139' (10 Holes)
Break down perfs w/ SPIT tool, All Open, Set tool @ 4020', RU to swab. Recover Spent Acid, Paraffin, & Water, w/ good Gas Flow
SITP = 1020 psi, COOH w/ tool. RU Smith Energy to Frac Upper Coal. Frac w/ 10K 40/70 sand and 11,290# 20/40 sand in 70Q N2 Foam
Well pressuring out, out N2, flush w/ linear gel and 5ppg. Blender sand concentration. ISIP 3600 psi. SI 2 hrs, Open well on 1/4" choke. Recovered
Plugs of Paraffin & Coal fines, GIH w/ tubing tagged sand bridge at 4118', GIH and retrieve RBP
Recover Frac Sand Coal fines and Paraffin. Cleanout to PBTD. Landed 2-7/8" tubing at 4282'. RD Release Bayless Rig # 6. RU Swab Unit. Swab Well
Recover Coal Fines, & Paraffin. 10-20-90 RU Big A # 5. Run 2" x 1-1/4" pump & 169 rods w/ 2 porvs.

Cement Squeeze

10-25-90 RU Bayless # 6. Pull Rods & Pump, RU Basin, Set RBP @ 1715', Test to 1000 psi, Perforate 2 holes at 1560', Pump into holes. RU Howco.
Pump 300 sxs B cement w/ 0.6% Halad 322, Displace w/ water to 1460'. Displaced at 1 BPM 2000 psi, Ran Temp Survey found TOC @ 500' +/-
DO cement, Test to 1000 psi, Recover RBP. Land tubing & New Pump Same Depths.

Nitrogen Cleanout & Acidize

06-19-91 RU R&S Rig # 27. LD Pump & Rods, Pull & LD 2 its tubing. Install 2-7/8" valve. Reverse Circulate w/ 160 deg N2, recover 25% Paraffin, Reverse w/ 80 bbls 160 deg water
Recover Paraffin, Unload w/ N2. SI tubing, Pump 750 gals 20% HCl acid w/ N2 heated to 160 degs, Displace w/ N2 Foam @ 150 degs, SI 30 mins.
Flowback thru tubing. Recovering Large amount of Coal Fines and Paraffin, Install Plunger and Piston Catcher. SICP 650 psi. Swab Well and Trip Piston w/ same recovery. Recover
10% Paraffin w/ Coal Fines. 07-05-91 Piston Recovering 15% Paraffin, 5% Oil, 11 bbls H2O & 90 MCFD.

Formation Name: Ojo Alamo & Nacimiento

10-09-95 RU Big A # 11, LD Rods & Pump, Could not circulate out Paraffin w/ 90 bbls water. RU Blue Jet, Run GR-NEU-GSL log. Set CIBP @ 4000', FL @ 2870'.
PT RBP to 1600 psi. RU BJ Services. Spot 1200 gals 7-1/2% HCl at 3818'. RU Basin to Perforate 1 SPF @ 2609', 2614', 2736', 2741', 2853', 2877', 2880', 2941', 2989', 2992'
3001', 3254', 3302', 3380', 3384', 3392', 3405', 3428', 3435', 3438', 3470', 3472', 3487', 3490', 3538', 3584', 3613', 3784', 3792', 3824' (30 Holes)
GIH w/ Halliburton PKR set at 2432', Acidize w/ 1500 gals 15% HCl w/ ball sealers. Good Breaks. Swabbed back w/ FL @ 2400'.
Set PKR @ 3689', and Swab Test made 4 runs, swabbed dry, Reset PKR @ 3340', FL constant at 2200'. COOH w/ PKR. GIH w/ BP & PKR Combination
Set RBP @ 3340', Swab Test 2609' to 3340', FL constant at 2200'. Set PKR @ 2494'. Swab test 2494' to 3340', FL constant at 2100'.
Move RBP to 3520', Set PKR @ 3340', Swab test 3340' to 3520', FL constant at 2100'. Release RBP, Set PKR @ 3520', Swab test 3520' to 3824', FL stable @ 2100'.
Reset PKR @ 3706', Swab Test 3706' to 3824', FL constant at 1800'. Set RBP @ 2920' & PKR @ 2790', Swab Test 2790'-2920', FL constant 1800' shows of gas. COOH w/ tools
10-10-95 Set CIBP @ 3700', Set Cmt Retainer at 3520'. Establish rate at 2 BPM 425 psi, Cement w/ 100 sxs (3538', 3584', 3613').
Tag cement at 2785', RU to swab, 7 runs swabbed dry. COOH w/ bit, GIH w/ PKR set at 2420'. PT to 1000 psi, bleeds off in 2 mins, Establish rate below 2420' of 2 BPM @ 1000 psi.
RU Halliburton. Cement w/ 50 sxs below PKR, Hesitate sqz to 1535 psi, displace to 2462', Test Csg to 1000 psi, Release PKR, Tag TOC @ 2474'. Onll out
Cement from 2474' to 2616', PT Csg to 1000 psi, GIH to 2785', DO cement from 2785' to 2795', PT to 1000 psi, GIH to 2805', Tag Cement, DO from 2805' to 2969'.
PT Casing to 1000 psi, Okay, Drilled Cement from 2969' to 3030', PT 1000 psi, Okay, DO from 3030' to 3340', PT 1000 psi, Okay, DO from 3340' to 3470', PT 1000 psi, Okay, DO from 3470' to 3472', PT 1000 psi, Okay, DO from 3472' to 3474', PT 1000 psi, Okay, DO from 3474' to 3476', PT 1000 psi, Okay, DO from 3476' to 3478', PT 1000 psi, Okay, DO from 3478' to 3480', PT 1000 psi, Okay, DO from 3480' to 3482', PT 1000 psi, Okay, DO from 3482' to 3484', PT 1000 psi, Okay, DO from 3484' to 3486', PT 1000 psi, Okay, DO from 3486' to 3488', PT 1000 psi, Okay, DO from 3488' to 3490', PT 1000 psi, Okay, DO from 3490' to 3492', PT 1000 psi, Okay, DO from 3492' to 3494', PT 1000 psi, Okay, DO from 3494' to 3496', PT 1000 psi, Okay, DO from 3496' to 3498', PT 1000 psi, Okay, DO from 3498' to 3500', PT 1000 psi, Okay, DO from 3500' to 3502', PT 1000 psi, Okay, DO from 3502' to 3504', PT 1000 psi, Okay, DO from 3504' to 3506', PT 1000 psi, Okay, DO from 3506' to 3508', PT 1000 psi, Okay, DO from 3508' to 3510', PT 1000 psi, Okay, DO from 3510' to 3512', PT 1000 psi, Okay, DO from 3512' to 3514', PT 1000 psi, Okay, DO from 3514' to 3516', PT 1000 psi, Okay, DO from 3516' to 3518', PT 1000 psi, Okay, DO from 3518' to 3520', PT 1000 psi, Okay, DO from 3520' to 3522', PT 1000 psi, Okay, DO from 3522' to 3524', PT 1000 psi, Okay, DO from 3524' to 3526', PT 1000 psi, Okay, DO from 3526' to 3528', PT 1000 psi, Okay, DO from 3528' to 3530', PT 1000 psi, Okay, DO from 3530' to 3532', PT 1000 psi, Okay, DO from 3532' to 3534', PT 1000 psi, Okay, DO from 3534' to 3536', PT 1000 psi, Okay, DO from 3536' to 3538', PT 1000 psi, Okay, DO from 3538' to 3540', PT 1000 psi, Okay, DO from 3540' to 3542', PT 1000 psi, Okay, DO from 3542' to 3544', PT 1000 psi, Okay, DO from 3544' to 3546', PT 1000 psi, Okay, DO from 3546' to 3548', PT 1000 psi, Okay, DO from 3548' to 3550', PT 1000 psi, Okay, DO from 3550' to 3552', PT 1000 psi, Okay, DO from 3552' to 3554', PT 1000 psi, Okay, DO from 3554' to 3556', PT 1000 psi, Okay, DO from 3556' to 3558', PT 1000 psi, Okay, DO from 3558' to 3560', PT 1000 psi, Okay, DO from 3560' to 3562', PT 1000 psi, Okay, DO from 3562' to 3564', PT 1000 psi, Okay, DO from 3564' to 3566', PT 1000 psi, Okay, DO from 3566' to 3568', PT 1000 psi, Okay, DO from 3568' to 3570', PT 1000 psi, Okay, DO from 3570' to 3572', PT 1000 psi, Okay, DO from 3572' to 3574', PT 1000 psi, Okay, DO from 3574' to 3576', PT 1000 psi, Okay, DO from 3576' to 3578', PT 1000 psi, Okay, DO from 3578' to 3580', PT 1000 psi, Okay, DO from 3580' to 3582', PT 1000 psi, Okay, DO from 3582' to 3584', PT 1000 psi, Okay, DO from 3584' to 3586', PT 1000 psi, Okay, DO from 3586' to 3588', PT 1000 psi, Okay, DO from 3588' to 3590', PT 1000 psi, Okay, DO from 3590' to 3592', PT 1000 psi, Okay, DO from 3592' to 3594', PT 1000 psi, Okay, DO from 3594' to 3596', PT 1000 psi, Okay, DO from 3596' to 3598', PT 1000 psi, Okay, DO from 3598' to 3600', PT 1000 psi, Okay, DO from 3600' to 3602', PT 1000 psi, Okay, DO from 3602' to 3604', PT 1000 psi, Okay, DO from 3604' to 3606', PT 1000 psi, Okay, DO from 3606' to 3608', PT 1000 psi, Okay, DO from 3608' to 3610', PT 1000 psi, Okay, DO from 3610' to 3612', PT 1000 psi, Okay, DO from 3612' to 3614', PT 1000 psi, Okay, DO from 3614' to 3616', PT 1000 psi, Okay, DO from 3616' to 3618', PT 1000 psi, Okay, DO from 3618' to 3620', PT 1000 psi, Okay, DO from 3620' to 3622', PT 1000 psi, Okay, DO from 3622' to 3624', PT 1000 psi, Okay, DO from 3624' to 3626', PT 1000 psi, Okay, DO from 3626' to 3628', PT 1000 psi, Okay, DO from 3628' to 3630', PT 1000 psi, Okay, DO from 3630' to 3632', PT 1000 psi, Okay, DO from 3632' to 3634', PT 1000 psi, Okay, DO from 3634' to 3636', PT 1000 psi, Okay, DO from 3636' to 3638', PT 1000 psi, Okay, DO from 3638' to 3640', PT 1000 psi, Okay, DO from 3640' to 3642', PT 1000 psi, Okay, DO from 3642' to 3644', PT 1000 psi, Okay, DO from 3644' to 3646', PT 1000 psi, Okay, DO from 3646' to 3648', PT 1000 psi, Okay, DO from 3648' to 3650', PT 1000 psi, Okay, DO from 3650' to 3652', PT 1000 psi, Okay, DO from 3652' to 3654', PT 1000 psi, Okay, DO from 3654' to 3656', PT 1000 psi, Okay, DO from 3656' to 3658', PT 1000 psi, Okay, DO from 3658' to 3660', PT 1000 psi, Okay, DO from 3660' to 3662', PT 1000 psi, Okay, DO from 3662' to 3664', PT 1000 psi, Okay, DO from 3664' to 3666', PT 1000 psi, Okay, DO from 3666' to 3668', PT 1000 psi, Okay, DO from 3668' to 3670', PT 1000 psi, Okay, DO from 3670' to 3672', PT 1000 psi, Okay, DO from 3672' to 3674', PT 1000 psi, Okay, DO from 3674' to 3676', PT 1000 psi, Okay, DO from 3676' to 3678', PT 1000 psi, Okay, DO from 3678' to 3680', PT 1000 psi, Okay, DO from 3680' to 3682', PT 1000 psi, Okay, DO from 3682' to 3684', PT 1000 psi, Okay, DO from 3684' to 3686', PT 1000 psi, Okay, DO from 3686' to 3688', PT 1000 psi, Okay, DO from 3688' to 3690', PT 1000 psi, Okay, DO from 3690' to 3692', PT 1000 psi, Okay, DO from 3692' to 3694', PT 1000 psi, Okay, DO from 3694' to 3696', PT 1000 psi, Okay, DO from 3696' to 3698', PT 1000 psi, Okay, DO from 3698' to 3700', PT 1000 psi, Okay, DO from 3700' to 3702', PT 1000 psi, Okay, DO from 3702' to 3704', PT 1000 psi, Okay, DO from 3704' to 3706', PT 1000 psi, Okay, DO from 3706' to 3708', PT 1000 psi, Okay, DO from 3708' to 3710', PT 1000 psi, Okay, DO from 3710' to 3712', PT 1000 psi, Okay, DO from 3712' to 3714', PT 1000 psi, Okay, DO from 3714' to 3716', PT 1000 psi, Okay, DO from 3716' to 3718', PT 1000 psi, Okay, DO from 3718' to 3720', PT 1000 psi, Okay, DO from 3720' to 3722', PT 1000 psi, Okay, DO from 3722' to 3724', PT 1000 psi, Okay, DO from 3724' to 3726', PT 1000 psi, Okay, DO from 3726' to 3728', PT 1000 psi, Okay, DO from 3728' to 3730', PT 1000 psi, Okay, DO from 3730' to 3732', PT 1000 psi, Okay, DO from 3732' to 3734', PT 1000 psi, Okay, DO from 3734' to 3736', PT 1000 psi, Okay, DO from 3736' to 3738', PT 1000 psi, Okay, DO from 3738' to 3740', PT 1000 psi, Okay, DO from 3740' to 3742', PT 1000 psi, Okay, DO from 3742' to 3744', PT 1000 psi, Okay, DO from 3744' to 3746', PT 1000 psi, Okay, DO from 3746' to 3748', PT 1000 psi, Okay, DO from 3748' to 3750', PT 1000 psi, Okay, DO from 3750' to 3752', PT 1000 psi, Okay, DO from 3752' to 3754', PT 1000 psi, Okay, DO from 3754' to 3756', PT 1000 psi, Okay, DO from 3756' to 3758', PT 1000 psi, Okay, DO from 3758' to 3760', PT 1000 psi, Okay, DO from 3760' to 3762', PT 1000 psi, Okay, DO from 3762' to 3764', PT 1000 psi, Okay, DO from 3764' to 3766', PT 1000 psi, Okay, DO from 3766' to 3768', PT 1000 psi, Okay, DO from 3768' to 3770', PT 1000 psi, Okay, DO from 3770' to 3772', PT 1000 psi, Okay, DO from 3772' to 3774', PT 1000 psi, Okay, DO from 3774' to 3776', PT 1000 psi, Okay, DO from 3776' to 3778', PT 1000 psi, Okay, DO from 3778' to 3780', PT 1000 psi, Okay, DO from 3780' to 3782', PT 1000 psi, Okay, DO from 3782' to 3784', PT 1000 psi, Okay, DO from 3784' to 3786', PT 1000 psi, Okay, DO from 3786' to 3788', PT 1000 psi, Okay, DO from 3788' to 3790', PT 1000 psi, Okay, DO from 3790' to 3792', PT 1000 psi, Okay, DO from 3792' to 3794', PT 1000 psi, Okay, DO from 3794' to 3796', PT 1000 psi, Okay, DO from 3796' to 3798', PT 1000 psi, Okay, DO from 3798' to 3800', PT 1000 psi, Okay, DO from 3800' to 3802', PT 1000 psi, Okay, DO from 3802' to 3804', PT 1000 psi, Okay, DO from 3804' to 3806', PT 1000 psi, Okay, DO from 3806' to 3808', PT 1000 psi, Okay, DO from 3808' to 3810', PT 1000 psi, Okay, DO from 3810' to 3812', PT 1000 psi, Okay, DO from 3812' to 3814', PT 1000 psi, Okay, DO from 3814' to 3816', PT 1000 psi, Okay, DO from 3816' to 3818', PT 1000 psi, Okay, DO from 3818' to 3820', PT 1000 psi, Okay, DO from 3820' to 3822', PT 1000 psi, Okay, DO from 3822' to 3824', PT 1000 psi, Okay, DO from 3824' to 3826', PT 1000 psi, Okay, DO from 3826' to 3828', PT 1000 psi, Okay, DO from 3828' to 3830', PT 1000 psi, Okay, DO from 3830' to 3832', PT 1000 psi, Okay, DO from 3832' to 3834', PT 1000 psi, Okay, DO from 3834' to 3836', PT 1000 psi, Okay, DO from 3836' to 3838', PT 1000 psi, Okay, DO from 3838' to 3840', PT 1000 psi, Okay, DO from 3840' to 3842', PT 1000 psi, Okay, DO from 3842' to 3844', PT 1000 psi, Okay, DO from 3844' to 3846', PT 1000 psi, Okay, DO from 3846' to 3848', PT 1000 psi, Okay, DO from 3848' to 3850', PT 1000 psi, Okay, DO from 3850' to 3852', PT 1000 psi, Okay, DO from 3852' to 3854', PT 1000 psi, Okay, DO from 3854' to 3856', PT 1000 psi, Okay, DO from 3856' to 3858', PT 1000 psi, Okay, DO from 3858' to 3860', PT 1000 psi, Okay, DO from 3860' to 3862', PT 1000 psi, Okay, DO from 3862' to 3864', PT 1000 psi, Okay, DO from 3864' to 3866', PT 1000 psi, Okay, DO from 3866' to 3868', PT 1000 psi, Okay, DO from 3868' to 3870', PT 1000 psi, Okay, DO from 3870' to 3872', PT 1000 psi, Okay, DO from 3872' to 3874', PT 1000 psi, Okay, DO from 3874' to 3876', PT 1000 psi, Okay, DO from 3876' to 3878', PT 1000 psi, Okay, DO from 3878' to 3880', PT 1000 psi, Okay, DO from 3880' to 3882', PT 1000 psi, Okay, DO from 3882' to 3884', PT 1000 psi, Okay, DO from 3884' to 3886', PT 1000 psi, Okay, DO from 3886' to 3888', PT 1000 psi, Okay, DO from 3888' to 3890', PT 1000 psi, Okay, DO from 3890' to 3892', PT 1000 psi, Okay, DO from 3892' to 3894', PT 1000 psi, Okay, DO from 3894' to 3896', PT 1000 psi, Okay, DO from 3896' to 3898', PT 1000 psi, Okay, DO from 3898' to 3900', PT 1000 psi, Okay, DO from 3900' to 3902', PT 1000 psi, Okay, DO from 3902' to 3904', PT 1000 psi, Okay, DO from 3904' to 3906', PT 1000 psi, Okay, DO from 3906' to 3908', PT 1000 psi, Okay, DO from 3908' to 3910', PT 1000 psi, Okay, DO from 3910' to 3912', PT 1000 psi, Okay, DO from 3912' to 3914', PT 1000 psi, Okay, DO from 3914' to 3916', PT 1000 psi, Okay, DO from 3916' to 3918', PT 1000 psi, Okay, DO from 3918' to 3920', PT 1000 psi, Okay, DO from 3920' to 3922', PT 1000 psi, Okay, DO from 3922' to 3924', PT 1000 psi, Okay, DO from 3924' to 3926', PT 1000 psi, Okay, DO from 3926' to 3928', PT 1000 psi, Okay, DO from 3928' to 3930', PT 1000 psi, Okay, DO from 3930' to 3932', PT 1000 psi, Okay, DO from 3932' to 3934', PT 1000 psi, Okay, DO from 3934' to 3936', PT 1000 psi, Okay, DO from 3936' to 3938', PT 1000 psi, Okay, DO from 3938' to 3940', PT 1000 psi, Okay, DO from 3940' to 3942', PT 1000 psi, Okay, DO from 3942' to 3944', PT 1000 psi, Okay, DO from 3944' to 3946', PT 1000 psi, Okay, DO from 3946' to 3948', PT 1000 psi, Okay, DO from 3948' to 3950', PT 1000 psi, Okay, DO from 3950' to 3952', PT 1000 psi, Okay, DO from 3952' to 3954', PT 1000 psi, Okay, DO from 3954' to 3956', PT 1000 psi, Okay, DO from 3956' to 3958', PT 1000 psi, Okay, DO from 3958' to 3960', PT 1000 psi, Okay, DO from 3960' to 3962', PT 1000 psi, Okay, DO from 3962' to 3964', PT 1000 psi, Okay, DO from 3964' to 3966', PT 1000 psi, Okay, DO from 3966' to 3968', PT 1000 psi, Okay, DO from 3968' to 3970', PT 1000 psi, Okay, DO from 3970' to 3972', PT 1000 psi, Okay, DO from 3972' to 3974', PT 1000 psi, Okay, DO from 3974' to 3976', PT 1000 psi, Okay, DO from 3976' to 3978', PT 1000 psi, Okay, DO from 3978' to 3980', PT 1000 psi, Okay, DO from 3980' to 3982', PT 1000 psi, Okay, DO from 3982' to 3984', PT 1000 psi, Okay, DO from 3984' to 3986', PT 1000 psi, Okay, DO from 3986' to 3988', PT 1000 psi, Okay, DO from 3988' to 3990', PT 1000 psi, Okay, DO from 3990' to 3992', PT 1000 psi, Okay, DO from 3992' to 3994', PT 1000 psi, Okay, DO from 3994' to 3996', PT 1000 psi, Okay, DO from 3996' to 3998', PT 1000 psi, Okay, DO from 3998' to 4000', PT 1000 psi, Okay, DO from 4000' to 4002', PT 1000 psi, Okay, DO from 4002' to 4004', PT 1000 psi, Okay, DO from 4004' to 4006', PT 1000 psi, Okay, DO from 4006' to 4008', PT 1000 psi, Okay, DO from 4008' to 4010', PT 1000 psi, Okay, DO from 4010' to 4012', PT 1000 psi, Okay, DO from 4012' to 4014', PT 1000 psi, Okay, DO from 4014' to 4016', PT 1000 psi, Okay, DO from 4016' to 4018', PT 1000 psi, Okay, DO from 4018' to 4020', PT 1000 psi, Okay, DO from 4020' to 4022', PT 1000 psi, Okay, DO from 4022' to 4024', PT 1000 psi, Okay, DO from 4024' to 4026', PT 1000 psi, Okay, DO from 4026' to 4028', PT 1000 psi, Okay, DO from 4028' to 4030', PT 1000 psi, Okay, DO from 4030' to 4032', PT 1000 psi, Okay, DO from 4032' to 4034', PT 1000 psi, Okay, DO from 4034' to 4036', PT 1000 psi, Okay, DO from 4036' to 4038', PT 1000 psi, Okay, DO from 4038' to 4040', PT 1000 psi, Okay, DO from 4040' to 4042', PT 1000 psi, Okay, DO from 4042' to 4044', PT 1000 psi, Okay, DO from 4044' to 4046', PT 1000 psi, Okay, DO from 4046' to 4048', PT 1000 psi, Okay, DO from 4048' to 4050', PT 1000 psi, Okay, DO from 4050' to 4052', PT 1000 psi, Okay, DO from 4052' to 4054', PT 1000 psi, Okay, DO from 4054' to 4056', PT 1000 psi, Okay, DO from 4056' to 4058', PT 1000 psi, Okay, DO from 4058' to 4060', PT 1000 psi, Okay, DO from 4060' to 4062', PT 1000 psi, Okay, DO from 4062' to 4064', PT 1000 psi, Okay, DO from 4064' to 4066', PT 1000 psi, Okay, DO from 4066' to 4068', PT 1000 psi, Okay, DO from 4068' to 4070', PT 1000 psi, Okay, DO from 4070' to 4072', PT 1000 psi, Okay, DO from 4072' to 4074', PT 1000 psi, Okay, DO from 4074' to 4076', PT 1000 psi, Okay, DO from 4076' to 4078', PT 1000 psi, Okay, DO from 4078' to 4080', PT 1000 psi, Okay, DO from 4080' to 4082', PT 1000 psi, Okay, DO from 4082' to 4084', PT 1000 psi, Okay, DO from 4084' to 4086', PT 1000 psi, Okay, DO from 4086' to 4088', PT 1000 psi, Okay, DO from 4088' to 4090', PT 1000 psi, Okay, DO from 4090' to 4092', PT 1000 psi, Okay, DO from 4092' to 4094', PT 1000 psi, Okay, DO from 4094' to 4096', PT 1000 psi, Okay, DO from 4096' to 4098', PT 1000 psi, Okay, DO from 4098' to 4100', PT 1000 psi, Okay, DO from 4100' to 4102', PT 1000 psi, Okay, DO from 4102' to 4104', PT 1000 psi, Okay, DO from 4104' to 4106', PT 1000 psi, Okay, DO from 4106' to 4108', PT 1000 psi, Okay, DO from

Needs to be updated for Work Performed

Nacimiento

08-15-2000 MIRU Key Rig # 30. COOH w/ rods. NU BOPE. Test same. RU Basin Perforators. RIH set **CIBP @ 2820'**. Dump bail 3 sxs cmt on top of plug. Test Ceg to 500 psi 30 minutes, good test. SQZ HOLE AT 1560' AND EIGHT (8) PERFORATIONS NOT BROKEN DOWN AS SUSPECTED PREVIOUSLY. PERFORATE ADDITIONAL NACIMIENTO PERFS FROM **2724' TO 2730'** (6') @ 2 SPF, AND **2602' TO 2608'** (6') @ 2 SPF. GIH W/ PACKER ON TBG. SET PKR AT 2796'. TEST TUBING AND CIBP TO 4000 PSI. GOOD TEST on plug. RELEASE PRESS. RESET PKR AT 2676'. BD Perfs from 2724' to 2741' (12 New + 4 Old) 16 Holes with Water. Broke @ 1600 psi. Acidize & Ball-Off with 250 gallons 10% Acetic Acid & 25 - 1.3 SG 7/8" RCN Ball Sealers. Ball Off to 5000 psi. Surge Off. Establish Rate of 2 BPM @ 450 psi. ISIP 310. ND BJ. Release PKR. Stand Back 2 Stands. Set PKR @ 2549'. Place 250 psi on Backside. RU BJ. Drop 6 balls Ahead. Run 250 gals 10% Acetic Acid and Total of 50 - 1.3 SG 7/8" RCN Balls. Displace. Saw Distinct Breakdown of upper holes at 2600 psi. Ball-Off Perfs to 4000 psi. Bleed off. Pump at 2 BPM @ 1200 psi. ISIP 250 psi. ND BJ Services. Release PKR. GIH w/ 2 Stands & PU 2 Jts. Knock Balls past all Perfs. Stand Back 3 Stands. Set PKR @ 2549'. Remove Tubing Collar. Install 2-9/16" 5000# Gate Valve. NU Flow Tee. Rig Crew Arrive. Rig Up BJ Services. Transfer Water between Tanks. Pressure Test BJ lines to 5000 psi. Good Test.

Frac Nacimiento Perforations From **2602' to 2609'** and **2714' to 2741'** (32 holes total) With 128 bbls Fluid & 198,000 SCF Nitrogen @ 20 BPM Total Rate, 5 BPM Liquid Rate, 7100 SCFM Nitrogen, Running 0.5 ppg @ the Blender (As slow as possible) or 0.125 ppg Downhole Concentration. Run 2,160 lbs 20/40 Super DC Resin Coated Sand. Run Sand Until Densimeter Reached Zero ppg. Flush With Foam. ATP of 2800 psi, Max 2900 psi ISIP 2000 psi, 5 Min 1500 psi. Well Logged Off. No Flow. Flowback Ptl increased approximately 20 bbls Overnight. Estimated Total Fluid Recovery 170 bbls. Shut Well In @ 10:15 Hrs. Plan to Move on to Next Zone (San Jose).

ND Flowback Assembly. ND 2-9/16" Frac Valve. Release Packer. COOH Laying Down 26 Joints of 2-7/8", Total of 31 Jts Out. COOH. RU Basin Perforators w/ Pack-Off. RIH w/ 5-1/2" Owen CIBP. Set **CIBP @ 2500'**, Covering Nacimiento Perforations. FL @ 1200'. Load Hole. PT CIBP & entire Casing to 500 psi. Good Test. RIH w/ 3-1/2" Dump Bail. Dump Bail 2 sxs of Cement on top of CIBP @ 2500'. POOH.

San Jose

Perforate San Jose from **1922' to 1928'** (6' - 12 holes), & **1906' to 1912'** (6' - 12 holes). PU & Run PKR. Set Packer at 1828'. BD San Jose Perforations with water at 1000 psi. Establish a rate of 1.5 BPM @ 1000 psi ISIP Zero. Release PKR. PU Tubing Hanger. ND Stripping Head, Land Hanger. Set Packer in 8,000# Compression @ 1828'. RD Key Rig # 30. 8/27/2000 SITP on San Jose is Zero psi. MIRU BJ Services PT Lines to 6500#. BD Perfs on Water. Good Breaks. Establish rate of 11.3 BPM @ 1450 psi. ISIP Zero. Fracture Stimulate San Jose Perforations From 1906' to 1928' with 2,040 lbs of 20/40 Super DC Resin Coated proppant in a total of 165 bbls 5# Gel and 174,000 SCF Nitrogen. Pump Liquid @ 5 BPM and Nitrogen at 6,000 SCFM. Total rate of 20 BPM at 75 Quality Foam. Sand at 0.1 ppg. Flush with 8 bbls Liquid & Nitrogen. ISIP = 1000 psi, 5 Min = 770 psi. Total Foam 25,242 gallons. RD BJ. Flowback Well. 09-04-2000 MIRU Swab Rig from Farmington. RU to Swab 2-7/8" Tubing. Swab tubing. Recover 18.8 bbls Tight Spot at 1100' +/- FL @ 1250' +/- parted swab line. Dropped 400' of line and Swab tools down the well. Tbg 90 psi. Attempt to fish tools. No Good. RD Release Swab Rig. 09-21-2000 MIRU Key # 17. SICP=SITP = zero. Pull P&R, Land 69 Jts 2-7/8" tubing w/ pumping assembly. GIH with production 2-7/8" tubing as follows: 1 jt, OE for mud anchor, perf sub, SN, and 68 joints 2-7/8" Tubing. Land Tubing at 2101.81' (69 jts total) ND BOPE. NU WH. X-O to run 7/8" rods. PU Energy Pump (2-1/2"x1-1/4"x14"x18" RHAC-2) Run in the hole on 81 - 7/8" rods. Space out pump. Hang on Horse Head. Check pump Action. RD RELEASE RIG. Rod pump San Jose Formation. Recover 160 bbls water per day. No gas. Take H2O sample. Well produced No Gas, and all Water at a rate of 170 BWPD for 2 weeks. WELL IS INACTIVE. EVALUATE FOR FURTHER PLANS.

Updated 06-19-2002
TEM



NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

GARY E. JOHNSON
Governor
Betty Rivera
Cabinet Secretary

Lori Wrotenbery
Director
Oil Conservation Division

Received

4/19/02

Certified Receipt #7001 1140 0000 4018 5103

April 11, 2002

SYNERGY OPERATING LLC
GLEN PAPP
PO BOX 5513
FARMINGTON NM 87499-5513

Re: Current Status of Oil and Gas Wells

In May of 2000, we first notified you of your inactive wells that were not in compliance. Attached is the current list of your inactive wells that are not in compliance. Please provide me with the current status of each of these wells.

Remember that the deadline for compliance is June 1, 2002, after which time other enforcement action will be taken.

If you have any questions, please call me at 505-334-6178, ext. 16.

Sincerely yours,

Charlie T. Perrin
Deputy Oil & Gas Inspector
cperrin@state.nm.us

Glen O. Papp

AZTEC	30-039-24673	29-4 CARSON 28 #001	SYNERGY OPERATING LLC K-28-29N-04W	G	03-1994	M
AZTEC	30-031-20640	CHITTUM PENISTAJA SW #001	SYNERGY OPERATING LLC P-36-20N-05W	S	NONE	K
AZTEC	30-045-07199	OMLER #006	SYNERGY OPERATING LLC B-25-28N-10W	G	03-1998	L