

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-045-24729

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE 'APPLICATION FOR PERMIT' (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
Phillips Petroleum Company

3. Address of Operator
300 W. Arrington, Suite 200, Farmington, N.M. 87401

7. Lease Name or Unit Agreement Name

San Juan 29-6 Unit

8. Well No.
236

9. Pool name or Wildcat
Basin Fruitland Coal

4. Well Location
Unit Letter K : 1784 Feet From The S Line and 1733 Feet From The W Line
Section 18 Township 29N Range 6W NMPM Rio Arriba County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
6272' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: OIL CON. DIV ☐
DIST. 3

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 7-03-90 - MIRU Aztec Well Service Rig No. 301. Spudded 12 1/4" hole at 5:00 P. M. Ran 9 5/8", 36#, K-55, ST&C casing & set at 290'. RU Howco & cement with 250 sx cl 'B' cem. with 3% CaCl₂ and 1/4# celloflake/sk. circ. 90 sx cem. Plug down at 1:30 A.M. Bumped plug with 800 psi. Float held. WOC 8 1/2 hrs. NU BOP & pressure tested to 1000 psi - held Okay.
- 7-06-90 - Ran 7", 23#, J-55, LT&C casing and set @ 2885'. RU Howco and cement with 500 sx 65/35 POZ w/12% gel & 1/4# gelflake/sk followed by 100 sx cl 'B' cem. with 1/4# gelflake/sk followed by 50 sx cl 'B' cem. with 0.75% CFR-3, Circ. 135 sx cement. Plug down. Did not bump plug. Float held. ND BOP and set 7" slips with 45,000#. RD and Released Rig
- 8-02-90 - Drake #26 - Ran 5 1/2", 23# P110, LT&C Casing set at 3135' KB. Top of liner at 2779'. RU Husky Wireline and ran GR/CCL.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Area Landman DATE 8-13-90
505
TYPE OR PRINT NAME A. J. Kieke, Jr. TELEPHONE NO. 599-3410

(This space for State Use)

Original Signed by **FRANK T. CHAVEZ**

APPROVED BY [Signature] TITLE SUPERVISOR DISTRICT 2 DATE AUG 16 1990

CONDITIONS OF APPROVAL, IF ANY: