

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-039-24767
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-289-38
7. Lease Name or Unit Agreement Name San Juan 29-6 Unit
8. Well No. 260
9. Pool name or Wildcat BASIN FRUITLAND COAL

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL, REDEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator PHILLIPS PETROLEUM COMPANY
3. Address of Operator 5525 HWY 64 NBU 3004, FARMINGTON, NM 87401	4. Well Location Unit Letter G : 1720 Feet From The North Line and 1436 Feet From The East Line Section 16 Township 29N Range 6W NMPM Rio Arriba County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6585' GL	

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud & Csg Report ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-18-92

MIRU Four Corners #6. Spud 12-1/4" hole @ 0400 hrs on 9-18-92. Ran 9-5/8", 36#, K-55 casing and set @ 282'. Halliburton cemented w/200 Sx Class B w/25#/sk Flocele & 3% CaCl2. Circ. 95 Sx to surface. WOC 9 hrs. NU BOP's and tested to 1500 psi - okay.

9-23-92

Ran 7", 23#, K-55 casing and set @ 3290'. Cemented w/425 Sx Class B cmt w/12% gel and 1/4#/sk Celloflake followed w/150 Sx Class B with 1/4#/sk Celloflake. Did not bump plug. Circulated 91 Bbls. RD & released rig @ 1630 hrs on 9/23/92.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. A. Allred TITLE Drilling Supervisor DATE 9-29-92
TYPE OR PRINT NAME R. A. Allred TELEPHONE NO. _____

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT # 3 DATE OCT 02 1992
CONDITIONS OF APPROVAL, IF ANY: