Form 3160-5 November 108 Formerly 9-3.	-
······································	-

WFLI

NAME OF OPERATOR

WELL X

SUBMIT IN TRIPLICATE. (Other Instructions

Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 18323

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

۱R۱	MENI	OF	IHE	INTERIOR	verse side)	
IDE	ALLOFI	AND	MAN	AGEMENT		

VACIALIS	NOTICES	AND	REPORTS	ON	WELL	C
ひいりいんし	INCLINED	AINU	KELOKIS	UN	VYELL	

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT..." for such proposals.)

7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 29-4 Carson 24

FALCON SEABOARD GAS COMPANY ADDRESS OF OPERATOR

OTHER

C/O Dave Simmons Box 48, Farmington, NM 87499

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.

840' FSL & 1065' FWL

10. FIELD AND POOL, OR WILDCAT

WBLL NO.

Basin Fruitland Coal Pool
11. SEC., T., R., M., OR BLE. AND
SURVEY OR ARMA

Sec. 24 291-4W 13. STATE Rio_Arriba New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7010' GL

NOTICE OF INTENTION TO PULL OR ALTER CASING STOOP OF ACIDIZE PERATO WEST CHANGE PLANS

SUBSEQUENT REPORT OF: WATER SHUT-OFF REPAIRING WELL FRACTURE TREATMENT SHOOTING OR ACIDIZING ABANDONMENT (Other) Spud, csg, cement surface (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

SCRIBL TO WORKER OF COMPLETED OF ERATIOS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any property work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and gones pertinent to this work.)

7-31-90 Arapahoe Rig # 7 moved on location. Spud 12-1/4" surface hole at 7:45PM. Drilled to 247' KB. (KB 13') Circulated hole. Ran 6 joints 8-5/8", 24#, K55 ST&C, R3 casing (230.90'). Landed casing with bottom at 244' KB. Cemented with 180 sacks (212.40 cf) Class "B" w/ 1/4#/sk. flocele and 2% CaCl₂. Circulated 5 bbls. cement to surface. Plug down at 2:30 AM 8-1-90.

8-1-90 WOC 12 hours. Pressure tested BOP and surface casing to 800 psig. for 30 minutes. Held okay.

AUG 2 8 1990

OIL CON. DIV. DIST. 3

I berohe coulds significant the forestine is true and correct		
R. D. Simmons	TITLE Agent	DATE 8-10-90
(This space for Federal or State office use)		ACCEPTED FOR RECORD
CONSIZIONS OF APPROVAL, IF ANY:	TITLE .	AUG 24 1990

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA