

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

(505) 599-3412

300 W. Arrington, Suite 200, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit G, 1574' FNL & 1397' FEL
Sec. 33, T29N, R5W

5. Lease Designation and Serial No.
NM-011348

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 29-5 Unit

8. Well Name and No.
223

9. API Well No.
30-039-24909

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other 5-1/2" Long String

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10-26-90

Four Corners Rig No. 5 ran 5-1/2", 15.50#, K-55, LT&C casing and set @ 3700.33'. RU Halliburton and cemented stage one with 40 Sx 65/35 Poz with 6% Gel and 5# Gilsonite/Sk with 1/4# Flocele/Sk and 2% CaCl₂ followed with 94 Sx Class B with 2% CaCl₂. Plugged down @ 6:45 AM. Circ. 15 Sx cement. Did not bump plug. WOC 3 hours and cemented stage two with 637 Sx 65/35 Poz with 6% Gel and 5# Gilsonite/Sk with 1/4# Flocele/Sk and 2% CaCl₂ followed with 60 Sx Class B with 2% CaCl₂. Plugged down @ 11:00 AM. Close D.V. tool with 2000 psi - held. Circ. 110 Sx cement. WOC 3 hours. PU BOP and set slips with 55,000#. RD and released rig @ 12:30 PM.

5 days cool @ 3/8/92

RECEIVED

JAN 18 1991

OIL CON. DIV
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed Gail Bergman for R.A. Beland

Title Drilling Supervisor

Date 10-29-90

(This space for Federal or State office use)

ACCEPTED FOR RECORD

Approved by _____
Conditions of approval, if any:

Title _____

JAN 11 1991

FARMINGTON RESOURCE AREA

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side