Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED			
Budget Bur	esu No.	1004-0135	
Expires:	March	31, 1993	

 Lease Designation and Serial No. NM-011349-A

## SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indiginal, Allottee or Tribe Name

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

. . , .

7. If Unit or CA, Agreement Designation

1. Type of Well		San Juan 29-5 Unit
Oil X Gas Other		8. Well Name and No.
2. Name of Operator		214
Phillips Petroleum Company		9. API Well No.
3. Address and Telephone No.	(505) 599-3412	30-039-24930
300 W. Arrington, Suite 200, Farm	nington, NM 87401	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		Basin Fruitland Coal
Unit G , 1532' FNL & 1363' FEL		11. County or Parish, State
Sec. 27 , T29 N, R 5 W		Rio Arriba, NM
12. CHECK APPROPRIATE BOX(s) TO INDICA	TE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBJECT TO THE TOTAL	TYPE OF ACTION	
Notice by Need	Abandonment	Change of Plans
_ UU ==D1 1 1091	Recompletion	New Construction
Subsequent Report EB1 1 1991	Plugging Back	Non-Routine Fracturing
Final Aban Oll NOON. DIV.	Casing Repair	Water Shut-Off
Final Aban More	Altering Casing	Conversion to Injection
DIST. 3	Other 5-1/2" Long String	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and	give pertinent dates, including estimated date of starting	any proposed work. If well is directionally drilled,
aine enhantace locations and memorial and an versus soften and	<b></b>	

10-30-90

Four Corners Rig No. 5 ran 5-1/2", 15.5 $\sharp$ , J-55, LT&C long string casing set @ 3883.02'. RU Western and cemented stage one w/28 Sx 65/35 Poz with 6% Ge1, $\sharp$ 5- Gilsonite, 1/4 $\sharp$  Flocele/Sk and 2% CaCl<sub>2</sub> followed with 100 Sx Class B cement with 2% CaCl<sub>2</sub>. Plugged down @ 4:45 PM on 10-31-90.. Bumped plug with 2000 psi. Did not circulate cement off top of stage collar.

10-31-90

Western cemented second stage w/722 Sx 65/35 Poz, 6% Gel, #5 Gilsonite/Sk, 1/4# Flocele/Sk and 2% CaCl<sub>2</sub> followed with 60 Sx Class B cement w/2% CaCl<sub>2</sub>. Plugged down @ 9:15 AM. Closed stage collar with 2500 psi. Circ. 126 Sx cement. Set slips w/50,000#. RD & released rig @ 10:30 AM on 10-31-90.

Stage /col 2 3151.18

	ACCEPTED TOP RECORD
(This apace for Federal or State office use)	JAN 29 1991
Approved by Conditions of approval, if say:	FARMINGTON RESOURCE AREA

Tide 18 U.S.C. Section 1001, makes it a crime for my person knowingly and willfully to make to any department or agency of the United States any false, recessors or fraudulest statements or representations as to any matter within its jurisdiction.