

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

PHILLIPS PETROLEUM COMPANY

3. Address and Telephone No.

300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit K, 1670' FSL & 1433' FWL  
Sec. 21, T29N, R6W

7. If Unit or CA, Agreement Designation

San Juan 29-6 Unit

8. Well Name and No.

205

9. API Well No.

30-039-24931

10. Field and Pool, or Exploratory Area  
Basin Fruitland Coal

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other As Per NTL-FRA-90-1

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1.

Date: 12-13-90 Time Started: 1135 Time Completed: 1247  
Hole Size 8-3/4" Casing Size 7" 23# J-55 New Casing Seat 3151.78 Ft.  
Turbo Centralizers at 2679', 2635', 2591'.  
Spring Type Centralizers at 3130', 3064', 2976', 2891', 2802'.  
Mud Flush 10 BBls, Spacer 10 Fresh Water.

Lead Slurry 500 Sx 65/35 Poz, 12% Gel, 1/4# Flocele/Sk, 11.7 ppg @ 2.3 Ft<sup>3</sup>/Sx yield.

Mid Slurry -----

Tail Slurry 150 Sx C1 G, 1/4# Flocele/Sk, 15.8 ppg @ 1.15 Ft<sup>3</sup>/Sk yield.

Displaced Plug with 120 BBls Fresh Water.

Volume Cement Circulated 146 Bbls/Sacks

Average Pressure 240 PSI, Average Rate 5.5 BPM, Bumped Plug with 1500 PSI.

14. I hereby certify that the foregoing is true and correct

R. A. Allred

Signed

Title Drilling Supervisor

Date 12-19-90

(This space for Federal or State office use)

Approved by  
Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

Date

JAN 17 1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side