Form 3160-5 (June 1990)

1. Type of Well

2. Name of Operator

OB Ges Other

## UNITED STATES DEPARTMENT OF THE INTERIOR **RUREAU OF LAND MANAGEMENT**

FORM APPROVED						
Budget Bureau No. 1004-0135						
Expires:	March 31, 1993					

5. Lesse Designation and Serial No.

NM-011349

" L: 10

...ZXICJ

8. Well Name and No.

9. API Well No.

6. If Indian, Allottee or Tribe Name

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

7. If Unit or CA, Agreement Designation

San Juan 29-5 Unit

201

Phillips Petroleum Compa	9. API Well No.		
3. Address and Telephone No.	30-039-24976  10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or Survey E	Description)	Basin Fruitland Coal	
unit K . 2067' FSL & 18	819' FWL	11. County or Parish, State	
Sec. 27 , 129N, R5 W		Rio Arriba, NM	
12. CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, REPO	ORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION	N	
Notice of Inter D) & C	Abandonment	Change of Plans	
	Recompletion	New Construction	
Subsequent Repth 43 JAN1 81	OO1	Non-Routine Fracturing	
-	l — ~ · ·	Water Shut-Off	
Final Abandoomes CIT CON	Altering Cosing	Conversion to Injection	
	↓ ↓ Dother	L Dispose Water	
DIST		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
13. Describe Proposed or Completed Operations (Clearly state a give subsurface locations and measured and area vertice)	Il pertinent details, and give pertinent dates, including estimated date of startical depths for all markers and zones pertinent to this work.)*	ing any proposed work. If well is directionally drilled,	

12-4-90 MIRU Aztec Well Service Rig No. 301. Spudded 121" hole @ 5:00 P.M. Ran 9 5/8", 36#, K-55, ST&C Casing set @ 285.61'. RU Halliburton and cemented w/250 SX Class B cement w/3% CaCl2 and 1/4 Flocele/SK. Circ. 71 SX cement. Plugged down @ 3:15 A.M. on 12-5-90. Bumped plug w/525 psi. WOC 10.5 hrs. NU BOP and pressure tested to 1000 psi-Okav.

14. I hereby certify that the foregoing is true and company Signed R A ATTIVE I	Tide	Drilling Super	visor	12-11-90	
(This space for Federal or State office use)	. 11de	ACCEPTED FOR RECORD			
Approved by		JAN 11 1991			
Tide 18 U.S.C. Section 1001, makes it a coins for any person knowings or representations as to any matter within in jurisdiction.	y and willful	By to make to any department or ago	acy of the FARMING	TOW RESOURCE AREA	t statements
or representations as to any matter within its justices.	*See Incl	ruction on Reverse Side	BY 2		