Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lesse Designation and Serial No.

NM-03040-A

6. If Indian, Allottee or Tribe Name

| SUNDRY | NOTICES AND REPORTS ON WELLS | |
|--------|------------------------------|--|
| | | |

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

| USB AT FLIGHT | 7. If Unit or CA, Agreement Designation | |
|--|---|--|
| SUBMIT IN TRIPLICATE | | |
| 1. Type of Well | San Juan 29-6 Unit | |
| Oil X Well Other | 8. Well Name and No. | |
| 2. Name of Operator | 244 | |
| Phillips Petroleum Company | 9. API Well No. | |
| 3. Address and Telephone No. (505) 599-3412 | 30-039-24978 | |
| 300 W. Arrington, Suite 200, Farmington, NM 87401 | 10. Field and Pool, or Exploratory Area | |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) | Basin Fruitland Coal | |
| Unit M , 969' FSL & 1040' FWL Sec. 31 , 129N, R 6W | 11. County or Parish, State | |
| sec. 51 , 1250, 00 | Rio Arriba, NM | |

| 12. | CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA | | | | | | |
|-----|--|---|---|--|--|--|--|
| | TYPE OF SUBMISSION | TYPE OF ACTION | | | | | |
| | Notice of Intent Subsequent Report Final Abandonment Notice | Abandonment Recompletion Plugging Back Casing Repair Ahering Casing Other | Change of Plans X New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) | | | | |

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-14-90

MIRU Aztec Well Service Rig No. 301. Spud 12-1/4" hole @ 5:00 PM. Ran 9-5/8", 36#, K-55, ST&C casing set @ 281.26'. RU Halliburton and cemented w/250 Sx Class B cement w/3% CaCl₂ and 1/4# Flocele/Sk. Circ 90 Sx cement. Plug down @ 1:00 AM on 11-15-90 and bumped plug w/1000 psi. WOC 7.5 hours. NU BOP and pressure tested to 1000 psi - okay.



| 14. I hereby certify that the foregoing is true and correct Signed R A 1 1 12.0 | Title | Drilling Supervise POR RECORD19-90 | | | |
|---|-------|------------------------------------|--|--|--|
| (This space for Federal or State office use) | Tide | JAN 0.3. 1991 | | | |
| Approved by | | FARMINGTON RESOURCE AREA | | | |
| Tide 18 U.S.C. Section 1001, makes it a crime for any gerson knowingly and willfully to make to any department or agency of the United States any little, fictitious or fraudulent statements | | | | | |