Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease	Designation	and	Scriet No

SUNDRY NOTICES	AND P	REPORTS	ON WELLS
----------------	-------	---------	----------

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

NM-80162

6. If Indian, Allorice of Tribe Name

SUBMI	7. If Unit or CA, Agreement Designation	
t. Type of Well Oil Gas Well Well Other 2. Name of Operator		San Juan 29-5 Unit 8. Well Name and No.
Phillips Petroleum Compa 3. Address and Telephone No.	(505) 500 2/10	224 9. API Well No.
Unit M, 1293' FSL & 736' Sec. 23, 129N, R 5W	•	10. Field and Pool, or Exploratory Area Basin Fruitland Coa 11. County or Parish, State
	s) TO INDICATE NATURE OF NOTICE, REPOR	Rio Arriba, NM T, OR OTHER DATA
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Mugging Back Casing Repair Altering Casing Other 5-1/2" Long String	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection
Describe Proposed or Completed Operations (Clearly state all give subsurface locations and measured and true vertical state of the subsurface locations and measured and true vertical state of the subsurface locations.)	pertinent details, and give pertinent dates, including estimated date of starting and depths for all markers and zones pertinent to this work.)	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) ny proposed work. If well is directionally drilled,

11-5-90

Four Corners Rig No. 5 ran 5-1/2", 15.5#, J-55, LT&C casing set @ 392#.75'. Stage tool at 3515'. RU Halliburton and circ. 45 min. Howco cemented stage one w/35 Sx 65/35 Poz, 6% gel, 5# Gilsonite, 1/4# Flocele/Sk and 2% CaCl₂ followed by 142 Sx Class B cement w/2% CaCl₂. Plug down on stage one @ 11:00 PM on 11-5-90. Bumped plug w/1500 psi. Circ. 105 Sx cement. Circ. 5 hours and cemented second stage w/671 Sx 65/35 Poz, 6% Gel, 5# Gilsonite, 1/4# Flocele and 2% CaCl₂ followed w/60 Sx Class B cement w/2% CaCl₂. Plug down @ 3:45 AM on 11-6-90. Closed stage collar w/2400 psi. Circ. 158 Sx cement. PU BOP and set slips w/48000#. RD and released rig @ 5:15 AM on 11-6-90.

DEC1 4 1930

OIL CON. D. DIST. 3

14. I hereby certify that the foregoing is true and correct Signed A Allypi	Title	Drilling Supervisor	11-6-90
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Tide	ACCEPTED FOR RECO	
Communication of approved, it may			DEC 07 1990

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United Shirt any activities of fractions of fractions of fractions as to any matter within its jurisdiction.