Form 3160-5 (Jun. 1990)

UNITE DEPARTMENT BUREAU OF LA

ED STATES	FORM APPROVED
OF THE INTERIOR	Budget Bureau No. 1004-0135 Expires: March 31, 1993
ND MANAGEMENT	C. Levis Deviantion and Serial Ma

5.	Lease	Designation	иd	Serial	No.
	SF	-08111	4		

SUNDRY NOTICES	SAND	REPORTS	ON	WELLS
----------------	------	---------	----	-------

SUNDRY NOTICES AND REPORTS ON WELLS		01 001111
Do not use this form for proposals to d	6. If Indian, Allottee or Tribe Name	
Use "APPLICATION FO	OR PERMIT—" for such proposals	·
SUBMI	7. If Unit or CA, Agreement Designation	
I. Type of Well		San Juan 29-5 Unit
Oil (X) Well Other		8. Well Name and No.
2. Name of Operator		219
Phillips Petroleum Company		9. API Well No.
3. Address and Telephone No.	on, NM 87401 (505) 599-3412	30-039-25081
5525 Hwy 64 NBU 3004, Farmingt 4. Location of Well (Footage, Sec., T., R., M., or Survey I	Basin Fruitland Coal	
Unit K, 1926' FSL & 1847' FWL		11. County or Parish, State
Sec. 4, T29N, R5W		
OUTON ADDRODDIATE DOV	(1) TO (1) DIO 177 117 117 117 117 117 117 117 117 11	Rio Arriba, NM
	(s) TO INDICATE NATURE OF NOTICE, REPO	
TYPE OF SUBMISSION	TYPE OF ACTION	l
Notice of Intent	Abandonment	Change of Plans
X Subsequent Report	Recompletion	New Construction
Subsequent Report	Plugging Back Casing Repair	Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	X Other Liner & Tubing	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
(.75" diam). Total of 264 hole	NOV 51992 OIL CON. DIV.	3269' KB. Seleased rig:
4. I hereby certify)that the foregoing is true and correct Signed (This space for Federal or State office use) Approved by Conditions of approval, if any:	Title Drilling Supervisor	Dete 10-29-92 Dete 400EPTED FOR RECORD
	mountains and attitude to the same of the	
representations as to any matter within its jurisdiction.	mowingly and willfully to make to any department or agency of the United	States any false, fictitious or fraudulent statements
	*See Instruction on Reverse Side	