Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No. SF-078343 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well San Juan 29-5 Unit Oil Gas Well 8. Well Name and No. 2. Name of Operator 230 9. API Well No. Phillips Petroleum Company 3. Address and Telephone No. 30-039-25226 (505) 599-3412 10. Field and Pool, or Exploratory Area 5525 Hwy 64 NBU 3004, Farmington, NM 87401 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Basin Fruitland Coal Unit A, 388' FNL & 179' FEL 11. County or Parish, State Sec. 5, T29N, R5W Rio Arriba, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction X Subsequent Report Plugging Back Non-Routine Fracturing Water Shut-Off Casing Repair Altering Casing Conversion to Injection Final Abandonment Notice __ Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. 0015 Time Started: Time Completed: Date: Hole Size 8-3/4" Casing Size 7" Casing Seat 3125 Ft: Turbo Centralizers at 2734', 2648', 2604' Spring Type Centralizers at 222', 1686', 1134', Mud Flush 10 Bbls, Spacer Fresh Water. Lead Slurry 400 Sx 65/35 Poz, 12% gel, 10% salt, 1/4#/Sk Flocele Mid Slurry___ Tail Slurry 150 Sx Class G, 2% CaCl, 1/4#/Sk Flocele Displaced Plug with 120 Bbls Fresh Water. Volume Cement Circulated 100 Bixks / Sacks 1500 PSI. Average Rate 5.8 BPM, Bumped Plug with Average Pressure Drilling Supervisor 10-29-92 (This space for Federal or State office use)

*See Instruction on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, sicilitions of fraudulent statements

or representations as to any matter within its jurisdiction.