UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	5.	Lease Number
		SF-079893A
GAS	6.	If Indian, All. or Tribe Name
	7.	Unit Agreement Name
Name of Operator		
MERIDIAN OIL	8.	Well Name & Number
Address & Phone No. of Operator		Brown #200
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No. 30-039-25382
4. Location of Well, Footage, Sec., T, R, M 190'FSL, 1915'FWL, Sec.31, T-29-N, R-4-W, NMPM	10.	Field and Pool Basin Frt Coal/
		Gobernador PC Ext
	11.	County and State Rio Arriba Co, NM
		·
CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REP		DATA
Type of Submission Type of Action Notice of Intent Abandonment Ch	hange of Pl	ans
	ew Construc	
	on-Routine	
Casing Repair Wa	ater Shut o	
Final Abandonment Altering Casing Co	onversion t	o Injection
X_ Other -		
3. Describe Proposed or Completed Operations		
8-3-94 Drill to TD @ 4550'. Log well. 8-4-94 Ran 103 jts 4 1/2" 10.5# K-55 STC csg, set @		
cmt w/0.75% CFS 1.5% Howco Suds, 0.25 pps w/135 sx Class "B" w/0.75% CFS, 2% calcium pps Flocele (159 cu.ft.). Circ 12 bbl cmt cmt w/2% calcium chloride cap (106 cu.ft.) Cmtd in BOP, could not set slips, cut off.	Flocele (1) m chloride, to surface). WOC. PT	177 cu.ft.). Tailed 5 pps Gilsonite, 0.25 . Pump 90 sx Class "B" csg to 3800 psi, OK. N
cmt w/0.75% CFS 1.5% Howco Suds, 0.25 pps w/135 sx Class "B" w/0.75% CFS, 2% calcium pps Flocele (159 cu.ft.). Circ 12 bbl cmt cmt w/2% calcium chloride cap (106 cu.ft.)	Flocele (1) m chloride, to surface). WOC. PT	177 cu.ft.). Tailed 5 pps Gilsonite, 0.25 Pump 90 sx Class "B" csg to 3800 psi, OK. Noteleased 3:00 a.m. 8-4-
cmt w/0.75% CFS 1.5% Howco Suds, 0.25 pps w/135 sx Class "B" w/0.75% CFS, 2% calcium pps Flocele (159 cu.ft.). Circ 12 bbl cmt cmt w/2% calcium chloride cap (106 cu.ft.) Cmtd in BOP, could not set slips, cut off.	Flocele (1) m chloride, to surface). WOC. PT . RD. Rig r	177 cu.ft.). Tailed 5 pps Gilsonite, 0.25 . Pump 90 sx Class "B" csg to 3800 psi, OK. Ni eleased 3:00 a.m. 8-4- PH AUG -8 PH
cmt w/0.75% CFS 1.5% Howco Suds, 0.25 pps w/135 sx Class "B" w/0.75% CFS, 2% calcium pps Flocele (159 cu.ft.). Circ 12 bbl cmt cmt w/2% calcium chloride cap (106 cu.ft.) Cmtd in BOP, could not set slips, cut off. AU6 1 2 1994 OIL CONo DIDETO 3	Flocele (1) m chloride, to surface). WOC. PT . RD. Rig r	177 cu.ft.). Tailed 5 pps Gilsonite, 0.25 Pump 90 sx Class "B" csg to 3800 psi, OK. N eleased 3:00 a.m. 8-4- 070 FASMINGT
cmt w/0.75% CFS 1.5% Howco Suds, 0.25 pps w/135 sx Class "B" w/0.75% CFS, 2% calcium pps Flocele (159 cu.ft.). Circ 12 bbl cmt cmt w/2% calcium chloride cap (106 cu.ft.) Cmtd in BOP, could not set slips, cut off. AUG 1 2 1994 OIL CON. DIDET. 3	Flocele (1) m chloride, to surface). WOC. PT . RD. Rig re	177 cu.ft.). Tailed 5 pps Gilsonite, 0.25 . Pump 90 sx Class "B" csg to 3800 psi, OK. Ni eleased 3:00 a.m. 8-4- PH AUG -8 PH
cmt w/0.75% CFS 1.5% Howco Suds, 0.25 pps w/135 sx Class "B" w/0.75% CFS, 2% calcium pps Flocele (159 cu.ft.). Circ 12 bbl cmt cmt w/2% calcium chloride cap (106 cu.ft.) Cmtd in BOP, could not set slips, cut off. AUG 1 2 1994 OIL COMo DI DUST. 3	Flocele (1) m chloride, to surface). WOC. PT . RD. Rig re	177 cu.ft.). Tailed 5 pps Gilsonite, 0.25 Pump 90 sx Class "B" csg to 3800 psi, OK. N eleased 3:00 a.m. 8-4- 070 FARMINGTON, NM RECEIVED
cmt w/0.75% CFS 1.5% Howco Suds, 0.25 pps w/135 sx Class "B" w/0.75% CFS, 2% calcium pps Flocele (159 cu.ft.). Circ 12 bbl cmt cmt w/2% calcium chloride cap (106 cu.ft.) Cmtd in BOP, could not set slips, cut off. AUG 1 2 1994 OIL CON. DIDET. 3	Flocele (1) m chloride, to surface). WOC. PT . RD. Rig re	177 cu.ft.). Tailed 5 pps Gilsonite, 0.25 . Pump 90 sx Class "B" csg to 3800 psi, OK. N eleased 3:00 a.m. 8-4- PH BLM