

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

SF-078278

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 29-6 Unit

8. Well Name and No.

S J 29-6 #227R

9. API Well No.

30-039-25418

10. Field and Pool, or exploratory Area

Basin Fruitland Coal

11. County or Parish, State

Rio Arriba, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

**Unit K, 2503' FSL & 1816' FWL
Section 14, T-29-N, R-6-W**

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other **7" casing**
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

RIH w/8-3/4" bit & drilled through cement to TD @ 3450'. RIH w/7", 23# K-55 8rd LT&C casing. Set casing @ 3437'(KB). RU Western and pumped 10 bbls mud flush and 10 bbls H2O followed by 500 sx (185 bbls) 65/35 POZ C1 B cement w/12% gel, 1/4#/sx celloseal, yeild 2.08 ft3/sx, 12.2 ppg, followed by 100 sx (31 bbls) C1 B cement w/12% CaCl2, 1/4#/sx celloseal, yield 1.18 ft3/sx, 15.6 ppg, displaced w/135 bbls H2O, circ. 200 sxs cement to pit, bumped plug w/1900 psi, ck float-OK, plug down @ 8:55 am 12/9/94. Job complete 9:30 am. RD Western. WOC. Set slips and NU BOPs. PT.

RECEIVED
DEC 20 1994

OIL CON. DIV.
DIST. 3

DEC 15 1994
11:45

14. I hereby certify that the foregoing is true and correct

Signed **[Signature]**

Title **Enviro./Regulatory Engineer**

Date **12-12-94**

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

COPIED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

DEC 17 1994

NMOCD

FARMINGTON DISTRICT OFFICE