

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

**OIL CONSERVATION DIVISION**

**DISTRICT I**

P.O. Box 1980, Hobbs NM 88241-1980

**DISTRICT II**

P.O. Drawer DD, Artesia, NM 88210

**DISTRICT III**

1000 Rio Brazos Rd., Aztec, NM 87410

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-039-25752
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-289-3
7. Lease Name or Unit Agreement Name 009256 San Juan 29-5 Unit
8. Well No. #10A
9. Pool name or Wildcat Blanco Mesaverde 72319
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6654' (prepared GL)

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER

017654

2. Name of Operator

Phillips Petroleum Company

3. Address of Operator

5525 Highway 64, NBU 3004, Farmington NM 87401

4. Well Location

Unit Letter F : 1640' Feet From The North Line and 1850' Feet From The West Line

Section

16

Township

29N

Range

5W

NMPM

Rio Arriba,

County

11.

**Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data**

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud report ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/1/97 MIRU Big A #37. Spud 12-1/4" hole @ 0230 hrs 12/2/97. Drilled ahead w/12 1/4" hole to 375'. RIH w/9-5/8" 36# K-55 casing and landed @ 367'. RU BJ to cement. Pumped 170 sx Class B cement w/2% CaCl2 with 1/4#/sx Cello-flake, mixed @ 15.6 ppg, 1.20 yeild (36 bbls/204 ft3) 2 bpm @ 100#. Displaced with 25 bbls water. Plug down @ 17:10 hrs 12/2/97. Circ. 10 bbl(56 ft3) cement to surface. WOC 7 hrs. NU BOPs and test - OK.

**RECEIVED**  
DEC - 8 1997

**OIL CON. DIV.**

**DIST. 3**

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Patsy Clugston*

TITLE

Regulatory Assistant

DATE

12-4-97

TYPE OR PRINT NAME

Patsy Clugston

TELEPHONE NO. 505-599-3454

(This space for State Use)

APPROVED BY ORIGINAL SIGNED BY ERNIE BUSCH

TITLE

DEPUTY OIL & GAS INSPECTOR, DIST. #3

DATE

DEC - 8 1997

CONDITIONS OF APPROVAL, IF ANY: