

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit P, 800' FSL & 920' FEL
Section 20, T29N, R5W

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-03188

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 29-5 Unit

8. Well Name and No.

BJ 29-5 Unit #57M

9. API Well No.

30-039-25833

10. Field and Pool, or exploratory Area

Basin Dakota
Blanco Mesaverde

11. County or Parish, State

Rio Arriba NM

RECEIVED
JAN 13 1999
505-599-3454
OIL CON. DIV
DIST. 3

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other 4-1/2" casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/6/98
RIH w/6-1/4" bit & tagged cement @ 3935'. Drilled out cement from 3935' to 3900'. Drilled ahead to 8100' (TD). COOH w/DP. GIH w/4-1/2", 11.6# N-80 casing and set @ 8099'. RU BJ to cement. Pumped 10 bbls 2% KCl, 20 bbls gel water & 10 bbls 2% KCl ahead, then pumped 304 sx (645 cf) 35/65 C1 H cement, 6% gel, 10#/sx BA-90, 5% FL-62 & 2% CD-32, mixed at 12.3 ppg w/2.12 yeild. Rate 5 bpm & @ 100 psi to 130 psi. Dropped plug & displaced with 115 bbls 2% KCl water. Plug down @ 1637 hrs 12/10/98. Estimated cement top @ 2600'. RD BJ. ND BOP, set slips & cut off casing. RU WH & PT - OK. RD & released rig @ 0600 hrs 12/11/98. Will perf and stimulate the Dakota interval at a later date.

RECEIVED
BLM
JAN-4 AM 11:40
FARMINGTON, NM

14. I hereby certify that the foregoing is true and correct

Signed Patsy Clayton Title Regulatory Assistant

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date 12/30/98

JAN 12 1999

FARMINGTON DISTRICT OFF

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

NMOC