

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

NM-03188

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 29-5 Unit

8. Well Name and No.

S.J. 29-5 #64M

9. API Well No.

30-039-25834

10. Field and Pool, or exploratory Area

Basin Dakota &  
Blanco Mesaverde

11. County or Parish, State

Rio Arriba, NM

SUBMIT IN TRIPLICATE

1. Type of Well

Oil Well  Gas Well  Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-598-1454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit E, 1850' FNL 7 790' FWL  
Section 21, T29N, R5W

RECEIVED  
OIL CON. DIV.  
DIST. 3  
JAN 13 1999

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

Notice of Intent  
 Subsequent Report  
 Final Abandonment Notice

TYPE OF ACTION

Abandonment  
 Recompletion  
 Plugging Back  
 Casing Repair  
 Altering Casing  
 Other 4-1/2" casing  
 Change of Plans  
 New Construction  
 Non-Routine Fracturing  
 Water Shut-Off  
 Conversion to Injection  
 Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

RIH w/6-1/4" bit & drill 5' of cement to shoe @ 3885'. Drilled out shoe to open hole @ 3928'. Drilled ahead with 6-1/4" bit & air hammer to TD (8063'). COOH. Hole wet, unable to dry up, couldn't survey or log. RIH w/4-1/2" 11.6# N-80 casing and set @ 8063'.

BJ BJ to cement. Pumped 10 bbls 2% KCL, 20 bbls mud flush & 10 bbls KCL ahead of 310 sx (657 cf) 35/65 POZ C1 H cement, 6% gel, 10#/sx BA-90, 0.2% CD-32, 0.5% FL-52. Mixed at 12.3 ppg w/2.12 yield, rate 6.7 bpm at 370 psi. Dropped plug & displaced with 7 bbls water & 121.6 bbls 2% KCL. Plug down @ 2245 hrs 12/22/98 with 1500 psi. Plug held good. RD BOP, choke & kill lines. Set slips & cut off casing. Put cap on well. RD & released rig 12/23/98. Will perf and stimulate the Dakota interval at a later date.

RECEIVED  
BLM  
JAN 14 11:40  
FARMINGTON, NM

14. I hereby certify that the foregoing is true and correct

Signed Felipe Olguin Title Regulatory Assistant

ACCEPTED FOR RECORD  
Date 12/30/98

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date JAN 12 1999

Conditions of approval, if any:

FARMINGTON DISTRICT OFFICE

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instruction on Reverse Side

NMOCD