Submit 3 Copies to Appropriate

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103

Revised 1-1-89 District Office OIL CONSERVATION DIVISION DISTRICT I WELL API NO. 2040 Pacheco St. P.O. Box 1980, Hobbs NM 88241-1980 30-039-26179 Santa Fe, NM 87505 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 FEE X STATE L **DISTRICT III** 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: San Juan 29-6 Unit 009257 ÓIL WELL □ 017654 8. Well No. 2. Name of Operator SJ 29-6 Unit #29B Phillips Petroleum Company 9. Pool name or Wildcat 3. Address of Operator Blanco MV - 72319: Basin DK - 71599 5525 Highway 64, NBU 3004, Farmington NM 87401 12.2 4. Well Location 1380' North 755 Feet From The Feet From The Line and Rio Arriba 29N Range Township 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6379 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. **SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO:** ALTERING CASING PLUG AND ABANDON REMEDIAL WORK PERFORM REMEDIAL WORK COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **CHANGE PLANS** TEMPORARILY ABANDON CASING TEST AND CEMENT JOB PULL OR ALTER CASING Spud Report OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 9/5/99 MIRU Key Energy #49. Spud 12-1/4" hole @ 1515 hours 9/5/99. Drilled ahead to 380'. Circ. hole clean. RIH w/9-5/8" 36#, J-55 casing and landed @ 378'. RU BJ to cement. Pumped 5 bbls FW, 10 bbls mud clean II and 10 bbls FW w/red dye. Then pumped 215 sx (258 cf) Class H cement w/2% CaCl2 & 1/4#/sx Cello-flake @ 15.6 ppg, a yield of 1.20. After pumped 24 bbls cement, PU & landed 9-5/8" casing @ 374' (new 9-5/8" TD). Released wooden plug & displaced w/27.75 bbls FW. Shut down pumping @ 1402 hours 9/6/99. Circulated 16 sx cement to surface. RD BJ. WOC. NU WH, BOP, lines and manifold. PT BOP, casing, lines and maniold to 200 psi for 3 minutes and then 2000 psi for 10 minutes. Good test. I hereby certify that the information above is true and complete to the best of my knowledge and belief. Regulatory Assistant SIGNATURE TELEPHONE NO. 505-599-3454 Patsy Clugston TYPE OR PRINT NAME (This space for State Use) DEPUTY OIL & GAS INSPECTOR, DIST. 45 ORIGINAL SIGNED BY CHARLIE T. PERPAN

APPROVED BY