

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

DISTRICT I

P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.

30-039-26300

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

009256

San Juan 29-5 Unit

8. Well No.

#60M

9. Pool name or Wildcat

Basin Dakota / Blanco Mesaverde

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Phillips Petroleum Company

3. Address of Operator

5525 Highway 64, NBU 3004, Farmington NM 87401

4. Well Location

Unit Letter

D

880'

Feet From The

North

Line and

325'

Feet From The

West

Line

Section

32

Township

29N

Range

5W


NMPM

Rio Arriba

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6487'



11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud Report ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/28/00 MIRU Key #47. Spud 12-1/4" hole @ 18:30 hrs. Drilled ahead w/12-1/4" hole to 340' Surface TD. RIH w/9-5/8", 36#, K-55 casing and landed @ 334'. RU BJ to cement. PT lines to 1500# held OK. Pump 5 bbls FW to Est. circ. Pump 10 bbls mud clean II. Pump 10 bbls FW spacer w/Dye. Pump 165 sxs (233 cu ft) Type 3 cmt w/2% CACL 2 + 1/4#sx CF @ 3.0 BPM & 65#, mixed @ 14.5 PPG & yield = 1.41 cu ft/sx. Drop wooden plug & displace w/23.5 bbls GW, Plug Down @ 9:45 hrs. Circ. 6 bbls (47 sxs) to surface. WOC 8 hrs. NU BOPs and test. Surface lines to 1500# - 10 min. Held OK. PT Csg, Blinds, pipe rams & manifold to 200# - 3 min. Held OK. & to 1500# for 10 min. Held OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Vickie Davis

TITLE Regulatory Assistant

DATE 3/31/00

TELEPHONE NO. 505 599-3454

TYPE OR PRINT NAME Vickie Davis

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERRIN

DEPUTY OIL & GAS INSPECTOR, DIST. 3 **MAR 31 2000**

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: