

District I
1625 N. French, Hobbs, NM 88240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-039-26339
5. Indicate Type Of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. E-289-46

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER _____	7. Lease Name or Unit Agreement Name San Juan 29-6 Unit 009257
b. Type of Completion: NEW WELL ☐ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☒ OTHER _____	8. Well No. SJ 29-6 Unit #94M
2. Name of Operator Phillips Petroleum Company 017654	9. Pool name or Wildcat Blanco Mesaverde - 72319
3. Address of Operator 5525 Highway 64, NBU 3004, Farmington, NM 87401	

4. Well Location
Unit Letter F : 2370' Feet From The North Line and 1845' Feet From The West Line

Section <u>16</u>	Township <u>29N</u>	Range <u>6W</u>	NMPM <u>Rio Arriba</u>	County
10. Date Spudded 7/26/00	11. Date T.D. Reached 8/2/00	12. Date Compl. (Ready to Prod.) 1/26/01	13. Elevations (DF & RKB, RT, GR, etc.) 6527' GL	14. Elev. Casinghead
15. Total Depth 7904'	16. Plug Back T.D. CIBP - 5935'	17. If Multiple Compl. How Many Zones? 2	18. Intervals Drilled By Rotary Tools <u>X</u>	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name Blanco Mesaverde - 4980' - 5698'				20. Was Directional Survey Made no
21. Type Electric and Other Logs Run GSL/GR & CBL				22. Was Well Cored no

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9-5/8"	36#, K-55	333'	12-1/4"	220 sx	10 bbls
7"	20#, J-55	3852'	8-3/4"	1st - Lead & Tail - 160 sx	
				2nd - Lead & Tail - 425 sx	surface
4-1/2"	11.6#, I-80	7904'	6-1/4"	1st - Lead & Tail - 205 sx	Corrected
				2nd - Lead & Tail - 135 sx	TOC @ 3610'(c

24. LINER RECORD				25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-3/8", 4.7#	5710'	n/a

26. Perforation record (interval, size, and number) Blanco Mesaverde @ 1spf .34" holes-5698, 5683, 5671, 5663, 5655, 5613, 5602, 5588, 5539, 5479, 5405, 5381, 5357, 5270, 5249, 5236, 5200, 5175, 5030, 4980=20 holes	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL 4980'-5698' 1500 gal 15% HCl 4980'-5698' 150,000 gal 70 Q foam & 83,720 # 20/40 Brown sand
---	---

28. PRODUCTION							
Date First Production SI		Production Method (Flowing, gas lift, pumping - Size and type pump) flowing				Well Status (Prod. or Shut-in) SI	
Date of Test 1/25/01	Hours Tested 1 hr - pitot	Choke Size 1/2"	Prod'n For Test Period	Oil - Bbl.	Gas - MCF 1221 mcfd	Water - Bbl. 5 bwpd	Gas - Oil Ratio
Flow Tubing Press. n/a	Casing Pressure flowing -180#	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF 1221 mcfd	Water - Bbl. 5 bwpd	Oil Gravity - API -(Corr.)	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SI waiting to first deliver						Test Witnessed By Al Rector	

30. List Attachments

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Patsy Clugston Printed Patsy Clugston Sr. Regulatory Clerk 1/30/01

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
T. Salt _____
B. Salt _____
T. Yates _____
T. 7 Rivers _____
T. Queen _____
T. Grayburg _____
T. San Andres _____
T. Glorieta _____
T. Paddock _____
T. Blinbry _____
T. Tubb _____
T. Drinkard _____
T. Abo _____
T. Wolfcamp _____
T. Penn _____
T. Cisco (Bough C) _____

T. Canyon _____
T. Strawn _____
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Delaware Sand _____
T. Bone Springs _____
T. _____
T. _____
T. _____
T. _____

Northeastern New Mexico

T. Ojo Alamo 2519
T. Kirtland-Fruitland 2694
T. Pictured Cliffs 3409
T. Cliff House 5179
T. Menefee 5269
T. Point Lookout 5574
T. Mancos 5909
T. Gallup 6834
Base Greenhorn 7564
T. Dakota 7754
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permain _____
T. Penn "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Otzte _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____
No. 2, from _____ to _____

No. 3, from _____ to _____
No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
No. 2, from _____ to _____ feet
No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
1329			Nacimiento				
2519	2694	175	Sandstone				
2694	3054	360	Shale & sandstone				
3054	3409	355	Shale & coal				
3409	3684	275	Marine Sands				
3674	5179	1505	Sandstone & shale				
5179	5269	90	Sandstone & shale				
5269	5574	305	Sandstone & shale				
5574	5909	335	Sandstone & shale				
5909	6834	925	Shale				
6834	7564	730	Sandstone & shale				
7564	7619	55	Limestone				
7619	7754	135	Sandstone & shale				
7754	7904	150	Sandstone & shale				
			Tops estimated -John Bircher				