Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

DOREMO OF EM	IN IN IN INCLUDENT	5. Lease Serial No.	
SUNDRY NOTICES	NMNM011348		
Do not use this form for abandoned well. Use Fort	6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE -	7. If Unit or CA/Agreement, Name and/or N		
1. Type of Well Oil Well X Gas Well Other	RECEIVED &	NMNM78415A & B 8. Well Name and No.	
2. Name of Operator Phillips Petroleum Company	SJ 29-5 Unit #59M 9. API Well No.		
3a. Address	3h) Phone No. (include area code)	30-039-26581	
5525 Highway 64, NBU 3004, Farmingt		10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey I	Description)	Basin Dakota and	
Unit I, 1898' FSL & 934' FEl	Blanco Mesaverde		
Section 31, T29N, R5W	11. County or Parish, State		
		Rio Arriba, NM	
12. CHECK APPROPRIATE	BOX(ES) TO INDICATE NATURE OF NOTICE, RE	PORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTIO	N	
Notice of Intent	Acidize Deepen Product	ion (Start/Resume) Water Shut-Off	
X Subsequent Report	Alter Casing Fracture Treat Reclams Casing Repair New Construction Reconn		
Final Abandonment Notice	Change Plans Plug and Abandon Tempor Convert to Injection Plug Back Water D	arily Abandon <u>report</u> Disposal	
If the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per following completion of the involved operations. I testing has been completed. Final Abandonment Metermined that the final site is ready for final inspect 2/3/02 MIRU w/8-3/4" bit & drill w/7", 20#, J-55 casing and set @ bbls FW and then 10 bbls FW w/dye Strength FM, 3#/sx CSE, 3% KCL, 0 Tail - 50 sx (70 cf - 12.46 bbl s Plug down @ 1100 hrs 2/6/02. Cir	y state all pertinent details, including estimated starting date of any polete horizontally, give subsurface locations and measured and true of formed or provide the Bond No. on file with BLM/BIA. Required fithe operation results in a multiple completion or recompletion in Notices shall be filed only after all requirements, including reclamation.) ed out cement shoe & then drilled ahead to 3695'. RU BJ to cement. Pumped a preflush ahead of Lead - 500 sx (1205 cf - 214.60 b .4% FL-25, 0.25#/sx Cello-flake, 4#/sx Phenolurry) Type 3, 1% CaCl2, 0.25/sx Cello-falk c. 10 bbls cement to surface. ND BOP, Set fold, & plug to 200 psi - low and 3000 psi h	vertical depths of all pertinent markers and zones d subsequent reports shall be filed within 30 day a new interval, a Form 3160-4 shall be filed oncition, have been completed, and the operator ha 3695'. Circ. hole. RIH of 10 bbls mud clean, 10 bl slurry) Premium Lite High o-seal, 5#/sx Gilsonite. e. Displaced w/148 bbls H20. slips and cut off casing.	

14. I hereby certify that the foregoing is true and correct Name (Printed Typed) Patsy Clugston	Title	Sr. Regulatory/Proration Clerk						
Jatsy Clesson	Date	2/8/02						
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								
Approved by	Title	Date						
Conditions of approval, if any, are attached. Approval of this notice does not warra certify that the applicant holds legal or equitable title to those rights in the subject which would entitle the applicant to conduct operations thereon.	nt or Office	e h 11						

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.