

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit P, 995' FSL & 1045' FEL  
Section 28, T29N, R6W

5. Lease Designation and Serial No.

NM-03471

6. If Indian, Allottee or Tribe Name

Nov 2: 07

7. If Unit or CA, Agreement Designation

San Juan 29-6 Unit

8. Well Name and No.

SJ 29-6 Unit #47M

9. API Well No.

30-039-27238

10. Field and Pool, or exploratory Area

Blanco Mesaverde and  
Basin Dakota

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud Report  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11/17/99

MIRU Key Energy #53. Spud 12-1/4" hole @ 11/17/99 @ 1830 hrs. Drilled ahead to 390'. Circ. hole. RIH w/9-5/8" 36#, K-55 casing and set @ 383'. RU BJ to cement. Pumped 10 bbls mud clean and 10 bbls water spacer w/red dye. Then pumped 195 sx (234 cf) Class H cement w/2% CaCl2 & 1/4#/sx Cello-flake, mixed at 15.6 ppg with a yield of 1.20. Dropped wood plug & displaced w/27.8 blbs FW. Had 8 bbls (44.9 cf) cement circulated to surface. WOC.

RU WH & BOP & chokes lines. PT casing, & rams to 200 psi for 3 minutes and 2000 psi for 10 minutes. Good test.

APD/ROW Process

14. I hereby certify that the foregoing is true and correct

Signed Patsy Clayton Title Regulatory Assistant Date 11/19/99

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_  
Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instruction on Reverse Side

NMOCD

FARMINGTON FIELD OFFICE  
BY 8-224