NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Poc	ol	Man	ico I	iosa Y	erde F	ormation) Mean	. Verde		County_	Ric	Arriba	
										Date of			
										We:			
										not comme		<u> </u>	
										6681		50941	
												ess	
Date	e of (Complet	ion:			Packe	r	Sir	ngle-Brad Reserve	enhead-G.	G. or	G.O. Dual	
			-					ED DATA		ori romp.			
Test	ted Th	rough	(P /		Choke)	HHH			a.	Type Tar	os		
	<u> </u>		F	low D	ata			Tubing	Data	Casing I)ąta	Γ	
No.	(T	ine)	(Or11	ice)				1	ł	Press.	1	Duration of Flow	
SI	S	ize	Si	ze	psig	h _w	F.	<u> </u>	°F.	,		Hr.	
$\frac{31}{1.}$			3/	A"		-		975 126	500	1107	 	2 }	
1. 2. 3.										003	<u> </u>	3 hours	
2 • +	·····								ļ				
4. 5.									 		 		
							77.077.047		_	·			
No.		efficie		$\sqrt{h_{\mathbf{w}}^{\mathbf{r}}}$			FLOW CALCULATI Flow Temp. Factor Ft					Rate of Flow Q-MCFPD @ 15.025 psia	
1.	12.3650		, V W		-	138	1.0098	-	0.9688	F _{pv}			
1. 2. 3. 4.													
4.													
5.													
as L ravi	iquid ty of	Hydroc Liquid	arbon l Hydr	ocarbo	ons -e ^{-s})		cf/bbldeg.	ALCU ATI	Speci	fic Gravi	ty Flow	rator Gas_ ing Fluid	
No.	P _w	osia)	Pt ²	Fc	Q	$(F_cQ)^2$	(F.	Q) ² -e ^{-s})	P _w 2	$P_c^2 - P_w^2$	Ca:		
2.						·····			802.0	451.2		2.775	
3.				_			_					_	
٠.											+		
COMP. LDDRI	ANY R	St Wed	Berger at the second	duy,	TAXABLE PARTY	Carra gton, l	MCFPD;	99	.75/ 2.15	<u> </u>			
	ESSED_							·		j	ill)	ED/-	
OMPA	ANI						REMA	RKS			41471	10	
							THEFT	-2013		(\	MAR 2	1 1958	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure ($P_{\rm W}$). MCF/da. @ 15.025 psia and 60° F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

	Pw cannot be taken because of manner of completion or condition
of	well, then Pw must be calculated by adding the pressure drop due
to	friction within the flow string to P _t .

0II. (CON	SE:	W/A	(T)	ON	م م	7. j. j	341	SS	101
Transport Co. S. C.	A merele v		- Andrews	••	•					
	Thorse				** ** :	5	3		****	al ta valid
الخرياسية	elin i seen	7 % 3 3 4 -1 -	,	111	. , ,		, e			-
	::- ::			*	* .*	•	164	~		