

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410

AZTEC NM 87410 (505) 334-6178 FAX: (505) 334-6170 mnrd.state.nm.us/ocd/District III/3distric.htm

This form is not to be used for reporting packer leakage tests in Southeast New Mexico



Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator P	hillips Petro	leum Co. 0176	54 Lease N	ame <u>Sar</u>	ı Jua	n 29-6 Unit	Well No35	
Location of	Well:Unit Letter	M Sec 1	5_Twp_291	N Rge 6W	<u>√</u> _AF	PI # 30-0 <u>39-823</u> 8	36	
	NAME OF RESERVOIR OR POOL		TYPE OF PROD. (Oil or Gas)		METHOD OF PROD. (Flow or Art. Lift)		PROD.MEDIUM (Tbg. or Csg.)	
Upper Completion	Mesaverde	esaverde		gas		flowing	tubing	
Lower Completion	Dakota					flowing	tubing	
		PRE-FL	OW SHUT-I	N PRESSUR	RE DA	TA		
Upper Completion	Hour, date snut-in 11/11/2000		Length of time shut-in 3 days		SI press. Psig		Stabilized? (Yes or No)	
Lower Completion	Hour, date shut-in 11/11/2000	ur, date shut-in 11/11/2000		Length of time shut-in 3 days		ss. Psig	Stabilized? (Yes or No) yes	
<u> </u>			FLOW TI	EST NO. 1	100	N. 12 N. 13		
Commenced at	(hour, date)*			Zone producing (Upper or Lower)				
TIME (hour,date)	LAPSED TIME SINCE*	PRESSU Upper Completion La	ower Completion	PROD. ZON TEMP.	E	RI	EMARKS	
11/15/00	24 hrs	285	322	-		Upper SI; flowed lower zone		
11/16/00	48 hrs	285	130			Upper SI; flow	ed lower zone	
Production ra	ate during test	I		<u> </u>				
Oil:		BOPD based	on	Bbls. in	l <u></u> -	Hours(GravGOR	
Gas:		MCFF	PD; Tested th	nru (Orifice or	r Mete	r):		
		MID-TE	EST SHUT-IN	N PRESSUR	E DAT	ΓΑ		
Upper Completion	Hour, date shut-in		Length of time shut-in		SI press psig		Stabilized? (Yes or No)	
Lower Completion	Hour, date shut-in		Length of time shut-in		SI press. psig		Stabilized? (Yes or No)	
			(Continue or	reverse side)			•	

FLOW TEST NO. 2

Commenced	d at (hour, date)	h i		Zone producing (Upper or Lowr):				
TIME (hour,date)	LAPSED TIME Since**	PRES: Upper Completion	Lower Completion	PROD. ZONE	REMARKS			
			<u></u>					
Oil:	ate during test	D based onMC	Bt FPD:Tested thru	ols. inHo (Orfice or Meter)	oursGravGOR			
Remarks:								
hereby certi	-	*	ontained is true a	nd complete to th	e bes of my knowledge.			
Approved	NOV 29	18	Operat	or Phillips P	etroleum Company			
	Oil Conservation [Ву	Jim Kens	nedy Jim Kennedy			
By		CHAPLE T. PERM	Title	Title Temporary Well Tester				
				•				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweigh pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wellowhich have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure: gauges the accuracy of which must be checked at least twice, once at the beginning and once at the endeach test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gardual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 day after completion of the test. Tests shall be filed with the Aztec District Office of th New Mexico oil Conservation Division on northwest new Mexico packer leakage Ter Form Revised 11-16-98 with all deadweight pressures indicated thereon as well a the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).