

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

3a. Indicate Type of Lease	
State ☒	Fee ☐
3. State Oil & Gas Lease No.	
E-5111-4	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐	GAS WELL ☒	OTHER ☐	7. Unit Agreement Name
Name of Operator			San Juan 29-7 Unit
Address of Operator			8. Farm or Lease Name
PO Box 4289, Farmington, NM 87499			San Juan 29-7 Unit
Location of Well			9. Well No.
UNIT LETTER <u>H</u> 1755 FEET FROM THE North LINE AND 1055 FEET FROM East LINE, SECTION 36 TOWNSHIP 29N RANGE 7W N.M.P.M.			10. Field and Pool, or Wildcat Basin Fruitland Coal
11. Elevation (Show whether DF, RT, GR, etc.)			12. County
6531'GL			Rio Arriba

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	
		OTHER ☐	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-02-88 Spudded well at 10:45 pm 12-02-88. Drilled to 221'. Ran 5 jts. 9 5/8", 32.3#, H-40 surface casing set at 221'. Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (177 cu.ft.). circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok.

12-07-88 TD 3393'. Ran 80 jts. 7", 20.0#, K-55 intermediate casing, 3381' set @ 3393'. Cemented with 30 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (58 cu.ft.), and 100 sks. Class "B" w/2% calcium chloride (118 cu.ft.), followed by 450 sks. Class "B" w/65/35 Poz with 6% gel, 2% calcium chloride and 0.5 cu.ft. perlite/sk. (869 cu.ft.) and 100 sx. Class "B" with 2% calcium chloride (118 cu.ft.). WOC 12 hours. Held 1200#/30 min. Circulated to surface.

3. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

APPROVED [Signature] TITLE Regulatory Affairs DATE 12-12-88

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT III DATE DEC 12 1988

CONDITIONS OF APPROVAL, IF ANY: