

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

RECEIVED
BLM

99 JUL - 7 5 PM 1999
Lead Number
SF-078425

1. Type of Well
GAS

070 FARMINGTON, NM
If Indian, All. or
Tribe Name

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1030' FNL, 970' FEL, Sec. 34, T-29-N, R-7-W, NMMPM

7. Unit Agreement Name

San Juan 29-7 Unit
Well Name & Number
San Juan 29-7 U #60
API Well No.
30-039-07501
Field and Pool
Blanco Mesaverde
County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other - Pay add	

13. Describe Proposed or Completed Operations

6-17-99 MIRU. ND WH. NU BOP. SDON.

6-18-99 TOOH w/168 jts 1 1/2" tbq. TIH w/CIBP, set @ 4820'. Ran CBL-CCL-GR, no cmt bond across Lewis interval. Attempt to load hole w/190 bbl 2% KCl wtr. Ran CBL-CCL-GR @ 3181-4820', TOC @ 4810' w/ 0-100% bond scattered throughout rest of 5 1/2" lnr. Ran TDT @ 3910-4820'. TOOH. SD for weekend. (Verbal approval to block squeeze @ 3910' & 4820' from Wayne Townsend, BLM).

6-21-99 Load hole w/wtr. PT csg to 750 psi, OK. TIH, perf 4 sqz holes @ 4794'. TOOH. TIH w/5 1/2" cmt retainer, set @ 4741'. Establish injection. Pump 25 sx Class "B" neat cmt below cmt retainer. Reverse circ 3 bbl cmt to surface. TOOH. TIH, perf 4 sqz holes @ 3850'. TOOH. TIH w/5 1/2" pkr, set @ 3712'. Load annulus w/wtr. Pressure up to 500 psi. Establish injection. Pump 25 sx Class "B" neat cmt below pkr. Displaced to 1 bbl short of pkr. Cmt locked up. Release pkr. Reverse circ 1 bbl cmt to surface. Reset pkr @ 3649'. Sqz to 1500 psi. WOC. SDON.

6-22-99 TOOH w/pkr. TIH w/4 3/4" bit, tag TOC @ 3704'. Drill cmt @ 3704-3854'. Load hole w/2% KCl wtr. PT csg to 750 psi, OK. TOOH. TIH, ran CBL @ 3750-3950' w/500 psi, 20-80% bond over logged interval. TIH w/4 3/4" bit to TOC @ 4710'. Drill cmt & cmt retainer @ 4741'. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 7/6/99
no

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any statement or representation to the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

AUG 04 1999

NMOCB

FARMINGTON FIELD OFFICE
BY [Signature]

6-23-99 TIH to 4800'. Load hole w/2% KCl. PT csg to 750 psi, OK. TOOH. TIH, ran CBL @ 4600-4820', TOC @ 4780', 60% bond. Perf lower Lewis w/2 SPF @ 4454-4464', 4520-4530', 4602-4612', 4644-4654', 4724-4734', 4756-4766' w/0.46 diameter holes. TIH w/5 1/2" RBP & pkr. Breakdown w/250 gal 10% acetic acid. TOOH w/RBP & pkr. SDON.

6-24-99 Blow well & CO. TOOH. TIH w/5 1/2" pkr, set @ 3207'. Frac lower Lewis w/110 bbl CO2, 45,000# 30/50 Ottawa sd. CO after frac.

6-25-99 Blow well & CO. TOOH w/pkr. TIH w/CIBP, set @ 4400'. Pump 20 bbl 2% KCl wtr. Perf upper Lewis w/2 SPF @ 4010-4020', 4200-4220', 4262-4272', 4330-4350'. PT CIBP to 3800 psi, OK. Break down upper Lewis w/10% acetic acid. Blow well & CO. TOOH. SDON.

6-26-99 Frac upper Lewis w/129 bbl CO2, 45,000# 30/50 Ottawa sd. CO after frac.

6-27-99 Blow well & CO.

6-28-99 Blow well & CO. TOOH. TIH w/4 3/4" mill to 4211'. Mill to CIBP @ 4400'. Mill out CIBP @ 4400'. TIH to 4770'. Blow well & CO.

6-29-99 Blow well & CO.

6-30-99 Blow well & CO. Mill out CIBP @ 4820'. Blow well & CO to PBTD @ 5570'.

7-1-99 TOOH. TIH w/176 jts 2 3/8" 4.7# J-55 EUE tbgs, landed @ 5489'. ND BOP. NU WH. RD. Rig released.