

# NEW MEXICO OIL CONSERVATION COMMISSION

## Santa Fe, New Mexico

### MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) <b>Workover</b>	<b>XX</b>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Farmington, New Mexico  
(Place)

March 17, 1964  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**El Paso Natural Gas Company** Luse Well No. 1 in K  
(Company or Operator) Lease (Unit)  
**NE** 1/4 **SW** 1/4 of Sec. 15, T. 29N, R. 7W, NMPM., Blanco Mesa Verde Pool  
(40-acre Subdivision)  
Rio Arriba County.

### FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Due to possible casing failure & bridge between tubing & casing, it is intended to repair this well in the following manner:

#### If tubing Can Be Pulled:

1. Pull tubing & set magnesium top drillable bridge plug at approximately 4760'.
2. Pressure test 5 1/2" casing to 1500 psi.
3. Run cement bond & corrosion inspection logs.
4. Run full string of 2 7/8" casing & cement, bringing cement up into 5 1/2" casing.
5. Perforate & fracture Mesa Verde and complete well.

#### If tubing cannot be Pulled:

1. Cut tubing off below 5 1/2" casing & pull.
2. Set Baker Model "B" cement retainer at approximately 4760' & squeeze upon hole.
3. Pressure test 5 1/2" casing to 1500 psi.
4. Run cement bond & corrosion inspection logs.
5. Set whipstock and drill to 5400'.
6. Complete as above.

Approved 3-17, 1964  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By E. S. Oberly

Title Sup. Dist. III

**El Paso Natural Gas Company**  
Company or Operator

By ORIGINAL SIGNED F. S. OBERLY  
Position Petroleum Engineer

Send Communications regarding well to: MAR 19 1964

Name E. S. Oberly

Address Box 990, Farmington, New Mexico

**RECEIVED**

**OIL CON. COM.**  
**DIST. 3**