

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

800' FNL 800' FEL, Sec.3, T-29-N, R-7-W, NMPM

5. Lease Number
SF-078945

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name
San Juan 29-7 Unit

8. Well Name & Number
San Juan 29-7 U#83

9. API Well No.
30-039-076850

10. Field and Pool
Blanco Mesaverde

11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment

Type of Action

☐ Abandonment ☐ Change of Plans
☐ Recompletion ☐ New Construction
☐ Plugging Back ☐ Non-Routine Fracturing
☐ Casing Repair ☐ Water Shut off
☐ Altering Casing ☐ Conversion to Injection
☒ Other -

13. Describe Proposed or Completed Operations

It is intended to run a spinner survey on the subject well according to the attached procedure.

RECEIVED
BLM
98 NOV 18 PM 12:55
070 FARMINGTON, NM

14. I hereby certify that the foregoing is true and correct.

Signed *Regina Shaw Hull* Title Regulatory Administrator Date 11/16/98
TLW

(This space for Federal or State Office use)

APPROVED BY /S/ Duane W. Spencer Title _____ Date NOV 30 1998

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

San Juan 29-7 Unit #83
Blanco Mesaverde
Unit A, Section 03, T29N, R07W
Rio Arriba County, New Mexico
Elevation 6822' GL, 6832' KB
LAT: 36.759506' Long: 107.551529'

Summary:

The San Juan 29-7 Unit #83 was spudded in July of 1953 and was originally completed open hole in the Point Lookout. In June of 1996, the well was sidetracked and completed in the Point Lookout, Menefee, Cliffhouse, and the Lewis. By running the spinner flowmeter, the percent contribution of the Lewis and of the individual zones within the Lewis can be determined. The data gathered in this sweep of spinner surveys will be combined with the spinner data gathered in the spring of 1998 to help determine the ideal stimulation design for the Lewis Shale.

Procedure:

1. Comply with all NMOCD, BLM, and BR regulations. Conduct daily safety meetings for all personnel on location.

DO NOT KILL WELL. ANY FLUIDS USED IN WELLBORE WILL INVALIDATE DATA NEEDED. IF FLUIDS ARE REQUIRED, CONTACT MICHELE QUISEL OR STEVE CAMPBELL TO DISCUSS ALTERNATIVES.

2. Inspect location and wellhead and install rig anchors prior to rig move if needed.
3. MOL, hold safety meeting and RU slickline unit. SI Master valve. ND bullplug on flowtee. RU full lubricator and test to 1500 psi. Open master valve. RIH w/slickline and set tubing choke in FN @ 6235 ' (1.81" I.D. bore). RD slickline unit. SI master valve.
4. RU workover unit. Check all safety equipment to insure proper location and working order. ND wellhead and NU 7-1/16" 3000 BOP, spool, stripping head and blooie line to pit. Continue to flow well through casing valve. Flow well through casing valve and blow well through blooie line to pit.
5. Strip 200 jts. 2-3/8" 4.7# J-55 tubing through stripping head and stand back. ND stripping head. SI rams on BOP.

THE WELL WILL REMAIN ON PRODUCTION DURING THE ENTIRE SPINNER SURVEY.

San Juan 29-7 Unit #83

Blanco Mesaverde

Unit A, Section 03, T29N, R07W

Rio Arriba County, New Mexico

Elevation 6822' GL, 6832' KB

LAT: 36.759506' Long: 107.551529'

6. RU Schlumberger. RU full lubricator and test to 1500 psi. Open rams on BOP and RIH w/ spinner flowmeter tool/GR/CCL. Correlate depth to GR/CCL logs provided by the engineer on location.
7. Take spinner survey readings at the following stations:
 - Station #1 **4585'** Top of Navajo City Chacra
 - Station #2 **4711'** Top of Otero Chacra
 - Station #3 **4860'** Top of Middle Bench of Otero Chacra
 - Station #4 **5240'** Top of Upper Cliff House
 - Station #5 **5442'** Top of Massive Cliff House
8. Tag bottom w/ spinner tool. POOH w/ spinner flowmeter tool/GR/CCL and SI rams on BOP. RD full lubricator. RD and release Schlumberger.
- 9A. If fill, TIH w/ 3-7/8" bit and CO to PBTD. TOOH.
9. NU stripping head. Open rams on BOP. Strip 200 jts. 2-3/8" 4.7# J-55 tubing w/ expendable check and seating nipple one joint off bottom through stripping head and land tubing @ 6267'. Pump off expendable check. ND stripping head, BOP, spool, and blooie line. NU wellhead. RD and release rig.
10. NU bullplug and flowtee. Open master valve and put well on production.