

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078943

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 29-7 Unit

8. FARM OR LEASE NAME

San Juan 29-7 Unit

9. WELL NO.

100

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., E., M., OR BLK. AND
SURVEY OR AREA

Sec. 6, T29N, R7W, NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Jerome P. McHugh

3. ADDRESS OF OPERATOR

Box 234, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

790' FSL, 950' FWL Sec. 6, T29N, R7W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6322 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work).*

Squadded 9:00 P.M. 12-11-66. Drilling 15" hole at 175'

Drilling 15" hole to 210' 1 1/4" - 210'

Run 6 jts. 10 3/4" 32.75# H-40 casing, set at 206' RKB. Cemented w/200 sx
class "A" 2% Ca cl. RKB 10:45 A.M. 12-12-66.

SMC Amco casing. T.B. 3314. Set at 3255'. Cemented w/300 sx Class A,
3/4 Col; 100 sx class "C" neat. RKB 8:20 P.M. 12-17-66.

Run 239 jts. 4 1/2" O.D. 11.6 & 10.5# J-55 SR STAG, GPAL cog.
T.B. 7639.17' set at 7639 RKB. Cemented w/150 sx class "C" 40% Diacol "D"
12 1/2% fine Gilsomite per sk and 100 sx class "C" with 20% salt per sk.
P.C.B. 6:30 P.M. 12-23-66. Middled up, released rig 9:00 P.M. 12-23-66

RECEIVED
FEB 3, 1967
OIL CON. COM.
DIST. 3

I hereby certify that the foregoing is true and correct

SIGNED *J. H. McHugh*

TITLE *Engineer*

DATE *1-30-67*

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

FEB 2 1967

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.