NO. OF COPIES RECEIVED	T-5-7	Form C-103
DISTRIBUTION	+	Supersedes Old
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
FILE	1/-	
U.S.G.S.		5a. Indicate Type of Lease
LAND OFFICE		State X Fee
OPERATOR	3	5. State Oil & Gas Lease No. E-5114-4
		F-2114-4
(DO NOT USE THIS P	SUNDRY NOTICES AND REPORTS ON WELLS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. IN PROPOSALS.)	
1. OIL GA	S X OTHER-	7. Unit Agreement Name San Juan 29-7 Unit
2. Name of Operator El Paso Nat	tural Gas Company	6. Form or Lease Name San Juan 29-7 Unit
3. Address of Operator		9. Well No.
PO Box 990	, Farmington, NM 87401	106
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER K	1650 FEET FROM THE SOUTH LINE AND 1840 FEET FROM	Basin Dakota
	2001 737	
THE West	LINE, SECTION 36 TOWNSHIP 29N RANGE 7W NMPM.	
	15. Elevation (Show whether DF, RT, GR, etc.) 6815 GL	12. County Rio Arriba
16.	City I de la Company de National Propose de Cal	Data Data
NOT	Check Appropriate Box To Indicate Nature of Notice, Report or Oth SUBSEQUENT	REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JQB	
	OTHER Perf 8	k Irac
OTHER		
17. Describe Proposed or (work) SEE RULE 1103	Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any propose
6-15-73	Tested surface casing to 600#/30 minutes-OK.	
6-21-73	TD 3887'. Ran 118 joints 7", 20#, KS intermediate casing, 3877' set at 3887'. Cemented with 272 cu.ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2420'.	
6-26-73	TD 8115'. Ran 264 joints of 4 1/2", 11.6 and 10.5#, KS production casing, 8103' set at 8115'. Float collar set at 8106'. Cemented with 651 cu.ft. cement. WOC 18 hours. Top of cement at 3500'.	
8-10-73	PBTD 8106'. Tested casing to 4000#-OK. Perf'd 7862', 7880', 7960', 7962', 7988', 8010', 8030' and 8072' with 1 shot per foot. Frac'd with 80,000# 40/60 sand and 105,546 gallons treated water. No ball drops. Flushed with 5418 gallons water.	

Drilling Clerk

SUPERVISOR DIST. #3

AUG 1 5 1973

CON COM August 13, 1973

DATE AUG 1 5 1973

Original Signed by Emery C. Arnold

CONDITIONS OF APPROVAL, IF ANY:

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.