

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.
3. ADDRESS OF OPERATOR
BOX 990, FARMINGTON, NEW MEXICO
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2020'N, 390'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)	<input type="checkbox"/>		<input type="checkbox"/>

5. LEASE
SF 078943-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 29-7 Unit
8. FARM OR LEASE NAME
San Juan 29-7 Unit
9. WELL NO.
89A
10. FIELD OR WILDCAT NAME
Blanco Mesa Verde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 7, T-29-N, R-7-W
NMPM
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6350' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/21/78: T.D. 5451'. Ran 85 joints 7", 20#, K-55 intermediate casing, 5438' set at 5451'. Cemented with 304 cu. ft. cement. WOC 12 hours; held 1200#/50 minutes. Top of cement at 2100'.

4/25/78: T.D. 5728'. Ran 76 joints 4 1/2", 10.5#, K-55 casing liner, 2446' set 5282-5728'. Float collar set at 5711'. Cemented with 424 cu. ft. cement. WOC 18 hours.

8/25/78: PBTD 5711'. Tested casing to 4000#, OK. Perfed 4751, 4772, 4798, 4837, 4852, 4863, 4871, 4878, 4885, 4890, 4900, 4913, 5017, 5024, 5082, 5088, 5143, 5149, 5157, 5185 with 1 SPZ. Fraced with 66,000# 20/40 sand and 132,000 gallons water. Flushed w/7060 gal. water. Perfed Lower and Mass. P.L. 5291, 5298, 5306, 5312, 5317, 5324, 5330, Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft. (OVER)

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Drilling Clerk DATE 9/1/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

SEP 11 1978

U.S. GEOLOGICAL SURVEY
DURANGO, COLO.

Statewide budgetary and/or accounting purposes to assist in certain administrative and reports of such operations when conducted, as indicated, on Federal and State funds, and to be included in the budgetary and/or accounting records of such State, on all funds in such State, pursuant to applicable State law and regulations. Any other non-related information regarding the execution of the first four items of the report to be submitted, particularly with regard to local, area, or regional operations, and if it is not a known or reasonably foreseeable source, may be excluded from the Federal report/State office.

Consent to the use of the information requested by the Bureau of Indian Affairs should be described in accordance with Federal requirements. Consult local or tribal officials for more information on Federal or Indian law.

[illegible]

5536, 5542, 5551, 5559, 5574, 5597, 5408, 5441, 5456, 5482, 5534, 5557, 5588, 5630, 5650, 5659 with 1 SPZ. Flaced with 65,000 ± 20/40 sand and 130,000 gallons water. Flushed with 7170 gal. water.