

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
P. Paso Natural Gas Company
3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1840'S, 1520'E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:


SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF-078425
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 29-7 Unit
8. FARM OR LEASE NAME
San Juan 29-7 Unit
9. WELL NO.
60A (MD)
10. FIELD OR WILDCAT NAME
Basin Dakota & Blanco MV
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 34, T-29-N, R-7-W NMPM
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6672' GL

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 9-5-80: TD 3742'. Ran 93 joints 9 5/8", 40#, N-80 intermediate casing 3730' set at 3742'. Cemented w/ 596 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement 2200'.
- 9-8-80: TD 6225'. Ran 63 joints 7", 23#, N-80 casing liner 2596' set 3627-6223'. Float collar set at 6142'. Cemented w/ 667 cu. ft. cement. WOC 18 hours.
- 9-11-80: TD 7880'. Ran 46 joints 4 1/2", 11.6#, K-55 casing liner 1789' set 6092-7881'. Float collar set at 7873'. Cemented w/ 314 cu. ft. cement. WOC 18 hours.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Perry Bradford TITLE Drilling Clerk DATE Sept. 16, 1980

RECEIVED FOR RECORD

(This space for Federal or State office use)

APPROVED BY COO
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

BY BW PERMITS DISTRICT

NMOCC