

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1840'S, 1520'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED
SEP 11 1981
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE

SF 078425

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 29-7 Unit

8. FARM OR LEASE NAME

San Juan 29-7 Unit

9. WELL NO.

60A (MD)

10. FIELD OR WILDCAT NAME

Blanco MV & Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 34, T-29-N, R-7-W
NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE


New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6672' GL

(NOTE: Report results of multiple completion of zone change on Form 9-330)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

PBTD 7873', Tested casing to 4500#, Held ok.

9-1-81: Perfed Dakota:

7709,7719,7731,7737,7811,7818,7842,7847,7859,7866' W/1 SPZ. Fraced w/ 122,000# 20/40 sand, 40,000# 10/20 sand, 90,000 gal. versagel. Flushed w/ 16,700 gal. wtr. Perfed Point Lookout: 5619,5624,5634,5643,5648,5660,5676,5680,5690,5699,5708,5740,5748,5753,5767,5802, 5822,5830,5866,5890,5908,5931,5950,5961,5974,6002,6021' W/1 SPZ. Fraced w/ 74,500# 20/40 sand, 91,800 gal. wtr. Flushed w/ 14,500 gal. wtr.

9-2-81: Perfed Mesa Verde:

5065,5071,5077,5112,5153,5173,5179,5201,5207,5213,5253,5273,5368' W/1 SPZ. Fraced w/ 40,000# 20/40 sand, 54,300 gal. wtr. Flushed w/ 13,600 gal. wtr.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. P. Lucas TITLE Drilling Clerk DATE Sept. 8, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCC

BY Sm