....

40.20

5. LEASE

UNITED STATES DEDARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	SF 078423
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 29-7 Unit 8. FARM OR LEASE NAME
1. oil gas G	San Juan 29-7 Unit 9. WELL NO.
2. NAME OF OPERATOR El Paso Natural Gas Company	44A (MD) 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR Box 289, Farmington, New Mexico 87401	Blanco MV, Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1640'S, 1120'E AT TOP PROD. INTERVAL:	AREA Sec. 17- T-29-N, R-7-W N.M.P.M. 12. COUNTY OR PARISH 13. STATE San Juan New Mexico
AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6668 GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9–330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating estimated date of starting any proposed work. If well is	difectionally officers give subsurface locations an
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertines. 5-79: Spudded well. Drilled surface hole.	ent to this work.)* asing 206' set at 220'. Cemente
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertined. Spudded well. Drilled surface hole. 	ent to this work.)* asing 206' set at 220'. Cemente
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertines. 2-79: Spudded well. Drilled surface hole. 2-79: Ran 5 joints 13 3/8", 48#, H-40 surface can w/325 cu. ft. cement. Circulated to surface.	ent to this work.)* asing 206' set at 220'. Cemente
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertined. 2-79: Spudded well. Drilled surface hole. 2-79: Ran 5 joints 13 3/8", 48#, H-40 surface can w/325 cu. ft. cement. Circulated to surface.	ent to this work.)* asing 206' set at 220'. Cemente
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertines. 2-79: Spudded well. Drilled surface hole. 2-79: Ran 5 joints 13 3/8", 48#, H-40 surface can w/325 cu. ft. cement. Circulated to surface.	asing 206' set at 220'. Cemente ace. WOC 12 hours;held 600#/30
 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertined. 179: Spudded well. Drilled surface hole. 179: Ran 5 joints 13 3/8", 48#, H-40 surface can w/325 cu. ft. cement. Circulated to surface minutes. Subsurface Safety Valve: Manu. and Type	ent to this work.)* asing 206' set at 220'. Cemente ace. WOC 12 hours;held 600#/30 C 9 1979 Set @F
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertines. 6-79: Spudded well. Drilled surface hole. 7-79: Ran 5 joints 13 3/8", 48#, H-40 surface can w/325 cu. ft. cement. Circulated to surfaminutes. Subsurface Safety Valve: Manu. and Type 18. I hereby pertine that the foregoing is true and correct signed.	c 9 1979 Set @ F
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine (5-79: Spudded well. Drilled surface hole. 7-79: Ran 5 joints 13 3/8", 48#, H-40 surface car w/325 cu. ft. cement. Circulated to surfaminutes. Subsurface Safety Valve: Manu. and Type 18. I hereby pertify that the foregoing is true and correct	control of this work.)* Asing 206' set at 220'. Cemente ace. WOC 12 hours; held 600#/30 C 9 1979 Set @ F Clerk DATE November 8, 1979 Office use)

*See Instructions on Reverse Side