

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

Box 289, Farmington, New Mexico

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1640'S, 1120'E

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF 078423

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
San Juan 29-7 Unit

8. FARM OR LEASE NAME  
San Juan 29-7 Unit

9. WELL NO.  
44A

10. FIELD OR WILDCAT NAME  
Blanco MV, Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 17, T-29-N, R-7-W  
N.M.P.M.

12. COUNTY OR PARISH San Juan 13. STATE New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6668' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-12-79: TD 3888'. Ran 97 joints 9 5/8", 40#, N-80 intermediate casing, 3876' set at 3888'. Cemented w/580 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement 2600'.

11-15-79: TD 6241'. Ran 63 joints 7", 23#, N-80 casing liner, 2495' set at 3746'-6241'. Flota collar set at 6199'. Cemented w/660 cu. ft. cement. WOC 18 hours.

11-19-79: TD 7956'. Ran 57 joints 4 1/2", 11.6#, K-55 casing liner 1863' set at 6093 - 7956'. Float collar set at 7948'. Cemented w/336 cu. ft. cement. WOC 18 hours.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. D. Duce TITLE Drilling Clerk DATE November 19, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.

NOV 28 1979