UNITED STATES

-	UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE SF 078425 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different eservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 29-7 Unit 8. FARM OR LEASE NAME
_	1. oil gas well other 2. NAME OF OPERATOR	San Juan 29-7 Unit 9. WELL NO. 30A (MD)
-	El Paso Natural Gas Company 3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, NM 87041	10. FIELD OR WILDCAT NAME Blanco MV & Basin DAkota 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 35, T-29-N, R-7-W
	4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	NMPM 12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico
ī	6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6605 GL
T F S F F M C	REPAIR WELL	2 (NOTE Report results of multiple completion or zone change on Form 9-830.) LOGICAL SURVEY NGTON, N. M. DIST. 3
:	17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent.	irectionally drilled, give subsurface locations and
3-7-80:	TD 3702'. Ran 90 joints 9 5/8", 40#, N-80 int 3702'. Cemented w/ 564 cu. ft. cement. WOC 1 Top of cement 3000'.	
3-11-80:	TD 6175'. Ran 62 joints 7", 23 $\#$, N-80 casing liner 2810' set 3532-6175'. Float collar set at 6087'. Cemented w/ 678 cu. ft. cement. WOC 18 hours.	
3-14-80:	TD 7843'. Ran 44 joints 4 1/2", 11.6#, K-55 p 6068-7843'. Cemented w/ 316 cu. ft. cement.	roduction casing 1774' set
:	Subsurface Safety Valve: Manu. and Type	Set @ Ft.

(This space for Federal or State office use)

18. I hereby certify that the foregoing is true and correct

AUG 25 1980

CONDITIONS OF FAROVECORDAY:

*See Instructions on Reverse Side

Described Title Drilling Clerk DATE