## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Forr	n Approved.	
Bud	get Bureau No	o. 42-R1424

5.	LEASE	
_	∕ SF	078503

	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
(Do	SUNDRY NOTICES AND REPORTS ON WELLS not use this form for proposals to drill or to deepen or plug back to a different rvoir, Use Form 9-331-C for such proposals.)		
	oil gas 🗔	8. FARM OR LEASE NAME San Juan 29-7 Unit	
	NAME OF OPERATOR	9. WELL NO. 112M	
3.	El Paso Natural Gas Company ADDRESS OF OPERATOR	Basin Dak. & Blanco MV	
ئے <u>۔</u> 4. ر	P.O. Box 289, Farmington, NM 87401  LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  790'N, 1650'W	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29, T-29-N, R-7-W NMPM	
	AT SURFACE: 1560 W AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Rio Arriba New Mexico  14. API NO.	
	CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
TES FRA SHC REP PUL MUI CHA	QUEST FOR APPROVAL TO:  SUBSEQUENT REPORT OF LET WATER SHUT-OFF  CTURE TREAT  DOT OR ACIDIZE  PAIR WELL  LTIPLE COMPLETE  ANGE ZONES  ANDON*  DET WITH THE PROVAL TO:  SUBSEQUENT REPORT OF LET WATER CASHON TO THE PAIR OF TH	Change on Form 9-330  CIL CON. COM.  DIST. 3	
17.	DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is different and true vertical depths for all markers and zones pertined	firectionally drilled, give subsurface locations and	
7-1-81:	PBTD 7627'. Tested Casing to 4500#, Held Ok 7357,7365,7371,7377,7383,7389,7395,7481,7506 W/1 SPZ. Fraced w/ 170,000# 20/40 sand, 120, gal. wtr.	5,7523,7528,7548,7555,7566,7572'	
7-2-81:	Perfed Lower & Massive Point Lookout: 5302,5307,5317,5324,5328,5332,5344,5360,5374 5654,5683,5702' W/1 SPZ. Fraced w/ 68,500# 2 w/ 13,900 gal. wtr.	4,5381,5388,5392,5397,5409,5424,5446, 20/40 sand, 137,000 gal. wtr. Flushed	
Sut	Perfed Cliff House & Menefee: 4733,4740,4760,4766,4785,4815,4822,4829,4836 5118,5150,5224,5230,5235,5254,5260,5266' W/ bsurface Safety Valve: Manu. and Type	5,4843,4870,4887,4893,4960,4986,5104, SPZ. Fraced w/ 82,000# 20/40 sand,	
18.	164,000 gal. wtr. Flushed w/ 12,900 gal. w Thereby certify that the foregoing is true and correct	vtr.	
SIG	NED N. G. Sured TITLE Drilling Cl		
	(This space for Federal or State of	fice use)	
APP	PROVED BY TITLE NDITIONS OF APPROVAL, IF ANY:	DATE	
COP	ADITIONS OF AFFROYAL, II ANT.	- AND PART FOR DEMOND	

**NMOCC** 

\*See Instructions on Reverse Side

JUL 09 198

