FARMINGTON DISTRICT

BY_

5. LEASE

SF 078423

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 29-7 Unit 8. FARM OR LEASE NAME
	1. oil 🖂 gas 🖂	San Juan29-7 Unit
	well Well KU other	9. WELL NO.
	2. NAME OF OPERATOR El Paso Natural Gas Company	86類 4 10. FIELD OR WILDCAT NAME
	3 ADDRESS OF OPERATOR	Blanco MV & Basin Dakota
	P.O. Box 289, Farmington, NM	11. SEC., T., R., M., OR BLK. AND SURVEY OR
	4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 17, T-29-N, R-7-W
	below.) AT SURFACE: 1780'N, 980'W	NMPM 12. COUNTY OR PARISH 13. STATE
	AT TOP PROD. INTERVAL:	Rio Arriba New Mexico
	AT TOTAL DEPTH:	14. API 0.
	16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
		15. ELEVATIONS (SHOW DF, KDB, AND WD)
	ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (elearly state including estimated date of starting any proposed work. If well is demeasured and true vertical depths for all markers and zones pertiner 1: TD 3889'. Ran 95 joints of 5/8", casing 3876' set at 3890'. Cemented WOC 12 hours; held 1200#/30 minutes.	ee all pertinent details, and give pertinent dates directionally drilled, give subsurface locations and int to this work.)* 40#, N-80 intermediate w/ 954 cu. ft. cement. Top of cement at 3300'. N-80 casing liner 2693'
1-8-81	: TD 8047'. Ran 46 joints of 4 1/2", set 6266'8047'. Float collar set a cement. WOC 18 hours.	11.6#, K-55 casing liner 1781't 8039'. Cemented w/ 336 cf.
	Subsurface Safety Valve: Manu. and Type	Set @ Ft.
	18. I hereby certify that the foregoing is true and correct	
	SIGNED V. J. Dille Drilling	Clerk _{ATE} April 9, 1981
(This space for Federal or State office use)		
		DATE
	CONDITIONS OF APPROVAL, IF ANY: NMOCC	ACCEPTED FOR RECORD
	*See Instructions on Reverse	APR 21 1981
	ace instructions on reverse	yide .