Form 3160-5 (November 1983)

UNITED STATES

SUBMIT IN TRIPLICATES

Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1085

(Formerly 9-351)	DEPARTMENT OF THE INTE		SF 078424
SUND (Do not use this fo	ORY NOTICES AND REPORTS orm for proposals to drill or to deepen or plu use "APPLICATION FOR PERMIT—" for suc	RECEIL L. V. E D	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS WELL WELL	OTHER	AUG 20 1985	7. UNIT AGREEMENT NAME San Juan 29-7 Unit
2. NAME OF OPERATOR E	l Paso Natural Gas Comp	BUREAU OF LAND MANAGEMENT	San Juan 29-7 Unit
3. Address of operator P	ost Office Box 4289,Far	rmington,NM 87499	9. WELL NO. 130
4. LOCATION OF AELL (Report location clearly and in accordance with any State requirements.* See also space 17 below. At surface 2025'S, 1400'W		10. FIELD AND POOL, OR WILDCAT Basin Dakota	
			11. SEC., T., B., M., OR BLE. AND Sec. 21, 1 -29-N, R-7 - N.M.P.M.
14. PERSHIT NO.	15. ELEVATIONS (Show whether	771 GL	Rio Arriba NM
16.	Check Appropriate Box To Indicate	Nature of Notice, Report, or O	ther Data
NOT	CICE OF INTENTION TO:	BUBSEQUE	ENT REPORT OF:
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACCUIZE DEPAIR WELL (Other)	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON® CHANGE PLANS	(Norx: Report results	ALTERING CASING ABANDONMENT* Inning Casing of multiple completion on Well tion Report and Log form.)
17. DESCRIBE PRODUSED OR CO proposed work. If w nent to this work.) *	OMPLETED OPERATIONS (Clearly state all pertined is directionally drilled, give subsurface lo	pent details, and give pertinent dates, seations and measured and true vertical	including estimated date of starting any depths for all markers and zones perti-
8-6 -85	TD 3893'. Ran 93 jt 3881' set @ 3893'. Poz, with 6% gel, 2% perlite (299 cu.ft.) calcium chloride (11 min. Top of cement	Cemented with 155 sk calcium chloride an followed by 100 sks 8 cu.ft.). WOC 12 h	cs. Class "B" 65/35 ad 1/2 cu.ft./sack
8-10-85	TD 8025'. Ran 200 j 8013' set @ 8025'. 250 sks. Class "B" w and 2#/tuf-plug per Class "B" with 0.5% gal./sk fluid loss a of cement by T.S. @	Float collar set @ 8/2% chemical extenders sack (508 cu.ft.) for dispersant, 0.3% radditive (118 cu.ft.) 3000'.	Cemented with er, 0.3% retarder, ollowed by 100 sks. retarder, and 0.2 woc 18 hours. Top
		OIL	CON. DIV. DIST. 3
8. I hereby certify that the	foregoing in true and correct		0.11.05

8-16-85 Drilling Clerk **ACCEPTED FOR RECORD** (This space for Federal or State office use) TITLE . APPROVED BY AUG 20 1985 CONDITIONS OF APPROVAL, IF ANY: MMOCA FARMINGTON RESOURCE AREA *See Instructions on Reverse Side