STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT This form is not to be used for reporting packer leakage tests in Southeast New Mexico


OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

	\mptota\	OII INC				Lease 3	AUL MAS	N 29-	7 (INT	T TT	Well No.	106M	
Operator Location	MERIDIAN	OIL INC	: —			Lease _		11 23	, 011.		_ 140.		-
	Unit C	Sect.	36	Twp. 0	29N	Rge.	007W	Count	y F	IO ARRIBA	4		
NAME OF RESER			ESER	VOIR OR POOL	TYPE OF PROD.		М	METHOD OF PROD.		PROD.	MEDIUM	7	
	7.7.4.2.5.7.4.5.5.4.7.5.4.7.5.7.5					(Oil or Gas)			(Flow or Art. Lift)		(Tbg.	or Csg.)	1
Upper) (FICALIFED	MESAVERDE					1			FLOW			7
Completion	MESAVER	DE				GAS					TUBIN	•	
Lower	DAKOTA					GAS F			FLOW		TUBING		7
Completion						GAS		FLOW					
				PRE-FLOW	SHUT-II	N PRESSU	RE DATA	-					_
Upper	Hour, date shut-in Length of time shut-in					SI press. psig Stabilized? (Ye			s or No)		7		
Completion	0830 8-2-96 1			100	100		1/0						
	127×50	8-2-1	9				***						-
Lower	1202	. 5	-/	フン		11	IN A	-		Voc	_		
Completion	16870	5-5-	160			9,	<u>'U' </u>			/(2)			_
r				F	LOW TE	EST NO. 1							
Commenced	at (hour,date)*						Zone producing (Upper or Lower)						\dashv
TIME	LAPSED TIME			PRI		PROD. ZO							
(hour,date) SINCE*			Upper Completion	ompletion	TE	TEMP		REMARKS			_		
	T		- 1	_ 15	١.,	. o. #	1		N	· 1			
1158-5	172	hra	. 1	138#	1 41	\mathcal{O}^{\perp}			1 L)Lo	Sens	*60	
1012 11.5	1 2	ſ		J.									
1818 8-6	:1 76	hak	j	124#	1 ユ	95#							1
10/2 7 1	1	100		160	+ ~	<u>. 1 - 2 - 4 +</u>				••			٦
	1170	1. ~	1	110#	7	$\mathbf{Q}^{\mu \nu}$			The	in i Dari		locario	g off with
(7CL 8-1	112	MACES			14		1		129	III CAR	30/10	10/7/4/	41, 200
	ļ						ļ		/ -	110.	- 0.44	C196	YXC # thr
<u> </u>	 				+				119	21C' • C 5	7 11/8	7701	14c / 1110
										1 - 1	# .		housed
									011	TIVE YE	:51,10	=19 C	ncuigec
1					1						,		'
									<u> </u>				
Production	rate during te	st											
Oil:	во	PD based o	n	Bbls.	in	Hou	rs		Grav.		GOR_		-
													
Gas:			_ MC	FPD; Tested thru	(Orifice	or Meter):							
_													
			_	MID-TEST	SHUT-I	N PRESSU	RE DAT	A	_	,			_
Upper	Hour, date shut-in Length of time shut-in					SI press. psig Stabilized			Stabilized? (Y	es or No)			
Completion				1		1							_
Lower	Hour, date si	nut-in		Length of time shu	at-in	SI press. p	sig			Stabilized? (Y	es or No)		
Completion	1			1						I			

(Continue on reverse side)



ELOW TECT NO 3

			TLOW IES.	1 NO. 2							
	t (hour,date)**			Zone producing (Upper or Lower):							
TIME	LAPSED TIME	PR	ESSURE	PROD. ZONE							
(hour.date)	SINCE**	Upper Completion	Lower Completion	TEMP.	REMARKS						
			<u> </u>								
		 	 								
		İ									
		 									
		-		1							
		<u> </u>			_						
		İ									
		 	 								
				i							
Production	ate during test		<u> </u>								
r roduction i	are during test										
Oil:	BOPD base	ed on	Bbls. in	Hours.	Grav.	GOR					
Gas:		MCFPD; To	sted thru (Orifice or	Meter):							
Remarks:											
				·····							
I hereby cer	tify that the informat	ion herein containe	d is true and complet	te to the best of my ki	nowledge -						
				a to the best of my k	nowledge.						
Approved	N.C	LV (5 1996	19	Luk	I I K	parces Inc.					
		LI (3 1880	- 19———	_ Operator \(\sum_{\text{\text{O}}} \)	ungen 1140	rouscio Vinc.					
New Mex	ina Oil C	D		\mathcal{A}	10 N-						
MEM MIST	ico Oil Conservation	Division		By delas delas							
Ву	Ĭ.	email lection.		Title Operation associate							
		THE PROPERTY									
	Deputy	C. 3 Gas Ins	pector	7							
Title			•	Date							
											

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after except that the previously produced zone shall remain shut-in while the zone which actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be connected on all multiple completions within seven days following recompletion and/or chemical or frac-ture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. both zones shall remain shur-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days if the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- 6.. Flow Test No. 2 shall be conducted even though no leak was indicated during flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1

- was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gaz zone.
- 8. The results of the above described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division of Northwest New Mexico Packer Leakage Test form Revised 10/01/78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).