

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL. OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. CEMENT ☐ Other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P. O. Box 4289, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)

At surface 1180'S 1070'E

At top prod. interval reported below

At total depth

RECEIVED

JAN 27 1986

FEB 03 1986

14. PERMIT NO. DATE ISSUED

OL 001 DIV

7. UNIT AGREEMENT NAME
San Juan 29-7 Unit

8. FARM OR LEASE NAME
San Juan 29-7 Unit

9. WELL NO.
56A

10. FIELD AND POOL OR WILDCAT
Blanco Mesa Verde

11. SEC. T. R. M. OR BLOCK AND SURVEY
OR AREA

Sec. 15, T-29-N, R-7-W
NMPM

12. COUNTY OR
PARISH
Rio Arriba

13. STATE
NM

15. DATE SPUDDED 12-18-85 16. DATE T.D. REACHED 12-26-85 17. DATE COMPL. (Ready to produce) 1-23-86 18. ELEVATIONS (OF. RAB. RT. GR. ETC.) * 6233' GL 19. ELEV. CASINGHEAD 6233'

20. TOTAL DEPTH, MD & TVD 5712' 21. PLUG. BACK T.D., MD & TVD 5683' 22. IF MULTIPLE COMPL. HOW MANY * One 23. INTERVALS DRILLED BY Rotary 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD) * 4803-5623' (Blanco Mesa Verde) 25. WAS DIRECTIONAL SURVEY MADE No

26. TYPE ELECTRIC AND OTHER LOGS RUN Temp. Log; Ind. Gamma-Ray Log; Comp. Density Sidewall Neutron; Temp S. 27. WAS WELL CORED No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3#	229'	12 1/4"	413 cu ft	
7"	23.0#	3435'	8 3/4"	413 cu ft	

29. LINER RECORD				30. TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)
4 1/2"	3275'	5710'	424 cu ft		2 3/8"	5575'

31. PERFORATION RECORD (Interval, size and number) Pressure test to 3500 psi-ok. Perf'd (Lower Pt. Lookout) 5392, 5406, 5411, 5418, 5463, 5483, 5512, 5536, 5592, 5598, 5606, 5623, w/12 SPZ. 2nd stage (Mass. Pt. Lookout) 5119, 5124, 5140, 5236, 5256, 5262, 5268, 5274, 5280.

32. ACID. SHOT. FRACTURE. CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5392-5623'	39,600# 20/40 sand & 94,550 gal slickwater
5119-5369'	44,000# 20/40 sand & 105,350 gal slickwater

* Continued perf's listed on back pg. 1 PRODUCTION 4803-5042' 29,000# 20/40 sand & 78,350 gal slickwater

DATE FIRST PRODUCTION 1-16-86 PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing - Capable of Comm. HC to be tested when connected. WELL STATUS (Shut-in) Shut in

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PRIM. FOR TEST PERIOD	OIL—BBL.	GAS—MCF	WATER—BBL.	GAS-OIL RATIO
1-23-86	SI 7 Days	0		0	0	0	0
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF	WATER—BBL.	OIL GRAVITY-API (CORR.)	
SI 678	SI 678		No Flow	No Flow	No Flow	0	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Shut in to be Sold TEST WITNESSED BY John Easley

35. LIST OF ATTACHMENTS Temp Survey ACCEPTED FOR RECORD

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records. SIGNED [Signature] TITLE Drilling Clerk DATE 1-24-86

*(See Instructions and Spaces for Additional Data on Reverse Side)

GEOLOGIC MARKERS

ELEVATION		TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	DEPTH	
						MEAS. DEPTH	TRUE VERT. DEPTH
Chacra	4027'	4798'	Gry fn grn silty, glauconitic sd stone w/drk gry shale	Chacra	4027'		
Mesa Verde	4798'	4914'	Gry, fine-grn, dense sil ss., carb sh & coal	Mesa Verde	4798'		
Menefee	4914'	5240'	Gry, fine-grn s, carb sh & coal	Menefee	4914'		
Point Lookout	5240'	5710'	Gry, very fine sil ss w/frequent sh breaks	Point Lookout	5240'		
=====							
* Continued Perf's:							
5286, 5292, 5311, 5324, 5330, 5340, 5356, 5364, 5369 w/18 SPZ. 3rd stage (C.H.) 4803, 4809, 4817, 4823, 4833, 4850, 4860, 4882, 4888, 4933, 4965, 4995, 5042 w/13 SPZ.							