

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	5. LEASE DESIGNATION AND SERIAL NO. SF 078424
2. NAME OF OPERATOR El Paso Natural Gas Company	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499	7. UNIT AGREEMENT NAME San Juan 29-7 Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1540'N, 1605'W	8. FARM OR LEASE NAME San Juan 29-7 Unit
	9. WELL NO. 45A
	10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 20, T-29-N, R- 7-W N.M.P.M.
14. PERMIT NO. JAN 30 1986	12. COUNTY OR PARISH Rio Arriba NM
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6901' GL	13. STATE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

NOTICE OF INTENTION TO:
TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

01-26-86 Set bridge plug at 4000'. Perforated two holes at base of Ojo Alamo at 2832'. Squeeze cemented with 115 sks. Class "B" with 2% calcium chloride (136 cu.ft.). Top of cement 2500' T.S.

01-27-86 Drilled out squeeze cement. Pressure tested to 2000 psi, ok. Cleaned out to PBTD.

RECEIVED
FEB 03 1986
OIL CON. DIV.,
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED Peggy D. Oak TITLE Drilling Clerk

DATE 01-30-86

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side

NMOCG