

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. UNIT AGREEMENT NAME San Juan 29-7 Unit
2. NAME OF OPERATOR El Paso Natural Gas Company	8. FARM OR LEASE NAME San Juan 29-7 Unit
3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499	9. WELL NO. 45E
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below) At surface 790'S, 790'W	10. FIELD AND POOL, OR WILDCAT Basin Dakota
11. PERMIT NO. DEC 13 1985	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 20, T-29-N, R-7-W N.M.P.M.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6578'GL	12. COUNTY OR PARISH Rio Arriba
	13. STATE NM

RECEIVED

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud Well

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-11-85 Spudded well at 3:00 p.m. 12-11-85. Drilled to 235'. Ran 5 jts. 9 5/8", 32.3#, H-40 surface casing set at 223'. Cemented with 115 sks. Class "B", with 1/4# gel-flake/sk, 3% calcium chloride, (136 cu.ft.). Circulated to surface. WOC 12 hours. Tested 600#/30 minutes, held ok.

RECEIVED
DEC 19 1985

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Clerk

DATE

12-12-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCC